

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

31388 Clearglide , Ideal	1-Quart Squeeze Bottle
Catalog Number	31388
Manufacturer	Ideal
Description	Lubricant, 1 QT Squeeze Bottle, Colorless, Slight Odor, Clearglide Lubricant, 1.09 Specific Gravity, +40 to +100 °F, 2.31 LB
Weight per unit	2.3 (lbs/each)
Product Category	Paint, Chemicals, Etc.
Features	
specific gravity	1.09
Dimensions and Weight Size	1
Descriptions	
Description	CLEARGLIDE, 1-QUART SQUEEZE BOTTLE
extra long description	IDEAL 31-388 ClearGlide Lubricant,I
Features Special Features	IDEAL ClearGlide Wire pulling lubricant is a polymer-based formula well suited for all electrical and datacom applications, and safe to use with all cable types. It is clear and colorless, and suitable for indoor as well as outdoor applications. This formula provides quick and easy clean up, and extraordinary lubricity for super-fast pulls. Its controlled evaporation rate is ideal for shorter runs. It remains stable over wide temperature ranges from 32°F to 180°F (0°C to 82°C) and dries to a semi-fluid fil Clear and colorless for quick and easy clean-up; Exceptional lubricity for super-fast pulls; Polymer-based formula perfect for all electrical and datacom applications; Safe to use with all cable types; Remains stable over wide temperature range; Dries to a
	semi-fluid film that won't clog conduit; Clings to cable throughout long pulls; Easy to apply by hand, brush, or pump; Environmentally safe - non-toxic, non-flammable, and non-corrosive
Manufacturer Information Brand	ldeal
GTIN	00783250348152
UPC	783250348152
Taxonomies, Classifications, and	
	WIRE LUBE, MARKERS, & TIES
Туре	Lubricant



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton		
Package	12	
Weight Per each		

Uses, Certifications, and Standards

standard	
----------	--

UL Listed