20



#### AQUAGUARD® SENSORS

# AG-1100+

### Magnetic Float Switch System for Metal Pans

Code	Description	Qty.
96100	Float Switch	30
CLASSIFIE	FEATURES	
c <b>(ՈՐ)</b> ns	<ul> <li>Easy, Drill-Free Installat</li> </ul>	tion
IND. CONT. EQ. 75MF	<ul> <li>Pull Up Test Knob</li> </ul>	
	<ul> <li>Protective Cover</li> </ul>	

· UL 508 Approved

US Patent

**Application** • The AG-1100+ is incredibly easy to install. It can be mounted to the drain pan in 10 seconds or less. Installation does not require any pre-drilling for screws. The AG-1100+ incorporates a protective cover to keep out insulation and debris that could prevent the float from rising.

• Normally Open 3rd Wire for Optional External Alarm, Digital Controller, or Energy Management System • Residential and Commercial • High Capacity 5 Amp, 24Volt AC Magnetic Float Switch



# AG-1200+

Description

### Magnetic Float Switch System for Metal & Plastic Pans

96106	Float Switch 30	)
c UL us IND. CONT. EQ. 75MF UL 508	FEATURES  Easy, Drill-Free Installation  Pull Up Test Knob  Protective Cover  UL 508 Approved	

Application • The AG-1200+ has all of the features of the 1100+ plus an innovative two-piece clamp design which allows it to be mounted to a metal secondary drain pan (without a lip) or a plastic secondary drain pan (with a lip) in 10 seconds or less, without screws or drilling. Protective cover keeps out insulation, pests and debris.

• Normally Open 3rd Wire for Optional External Alarm, Digital Controller, or Energy Management System • Residential and Commercial • High Capacity 5 Amp, 24Volt AC Magnetic Float Switch



Qty.

20



#### AQUAGUARD® SENSORS

# AG-1100+

### Magnetic Float Switch System for Metal Pans

Code	Description	Qty.
96100	Float Switch	30
CLASSIFIE	FEATURES	
c <b>(ՈՐ)</b> ns	<ul> <li>Easy, Drill-Free Installat</li> </ul>	tion
IND. CONT. EQ. 75MF	<ul> <li>Pull Up Test Knob</li> </ul>	
	<ul> <li>Protective Cover</li> </ul>	

· UL 508 Approved

US Patent

**Application** • The AG-1100+ is incredibly easy to install. It can be mounted to the drain pan in 10 seconds or less. Installation does not require any pre-drilling for screws. The AG-1100+ incorporates a protective cover to keep out insulation and debris that could prevent the float from rising.

• Normally Open 3rd Wire for Optional External Alarm, Digital Controller, or Energy Management System • Residential and Commercial • High Capacity 5 Amp, 24Volt AC Magnetic Float Switch



# AG-1200+

Description

### Magnetic Float Switch System for Metal & Plastic Pans

96106	Float Switch 30	)
c UL us IND. CONT. EQ. 75MF UL 508	FEATURES  Easy, Drill-Free Installation  Pull Up Test Knob  Protective Cover  UL 508 Approved	

Application • The AG-1200+ has all of the features of the 1100+ plus an innovative two-piece clamp design which allows it to be mounted to a metal secondary drain pan (without a lip) or a plastic secondary drain pan (with a lip) in 10 seconds or less, without screws or drilling. Protective cover keeps out insulation, pests and debris.

• Normally Open 3rd Wire for Optional External Alarm, Digital Controller, or Energy Management System • Residential and Commercial • High Capacity 5 Amp, 24Volt AC Magnetic Float Switch



Qty.