


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## **BRNSURGE Type BR 2 Pole Surge Arrester** *Eaton Corp*

Soon	
Catalog Number	BRNSURGE
Manufacturer	Eaton Corp
Description	Eaton Type BR Circuit Breaker Surge Protective Device, Two Pole Surge Protective Device
Weight per unit	1.0 (lbs/each)
Product Category	Distribution Equipment
eatures	
dimensions	3.6000 IN X 3.5000 IN X 2.2500 IN
Short Circuit Rating	10 kA
Dimensions and Weight	
Depth	3.6
Height	2.25
Width	3.5
Descriptions	
Description	TYPE BR 2 POLE SURGE ARRESTER
extra long description	ETN BRNSURGE Type BR 2 pole Surge A
Features	Eaton offers a comprehensive family of surge products for use a service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t
Long Description	Eaton Type BR circuit breaker surge protective device, Two Pole Surge Protective Device
Product Type	Type BR 2 Pole Surge Arrester
Manufacturer Information	
Brand	Eaton
GTIN	00786689353667
Manufacturers Part Number	BRNSURGE
UPC	786689353667

## **Taxonomies, Classifications, and Categories**

Category Description	Fault Sensing Breakers (AFCI/GFCI)
Туре	Plug on module surge protection device



Frequency Rating

standard

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	11
Uses, Certifications, and Standards	
Application	OtherResidential Bldgs & Facilities - Residential Bldgs & Facilities -
	Other

cUL Certified,UL 1449

50/60 Hz