

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

THHN600BK1000 THHN 600 STR Black 1000' Southwire Company



Manufacturer Southwire Company Description 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also Rated MTW. Simpull Technology For Easier Pulling. Weight per unit 2.0 (lbs/ft) Product Category THHN-190-STR (Stranded) Features	Catalog Number	THHN600BK1000
Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also Rated MTW. Simpull Technology For Easier Pulling. Weight per unit 2.0 (lbs/ft) Product Category THHN-T90-STR (Stranded) Features media media Yes Number of Conductors 1 Tip Size 1000 ft. Spool Dimensions and Weight Length Length 1000 Descriptions Eastrant Description THHN 600 STR BLACK 1000' extra long description SWC 32147106 THHN 600 Str Cu SIM BK Long Description 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. Special Features No Lube Manufacturer Information Brand Copper GTIN 0032886234460 UPC 032886234460 UPC 032886234460 UPC 032886234460 UPC 032886234460 UPC 032886234460 <	Manufacturer	Southwire Company
Product Category THHN-T90-STR (Stranded) Features wedia media Yes Number of Conductors 1 Tip Size 1000 ft. Spool Dimensions and Weight Length Length 1000 Descriptions Escription Description THHN 600 STR BLACK 1000' extra long description SWC 32147106 THHN 600 Str Cu SIM Bk Long Description 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. Special Features No Lube Manufacturer Information Brand Copper GTIN 00032886234460 UPC 032886234460 UPC 032886234460 UPC 032886234460 Type THHN-2 Availability minimum qty minimum qty 1000	Description	Sheath, Heat, Moisture, Gasoline and Oil Resistant Ii. Rated THHN and THWN-2. Also Rated MTW. Simpull Technology For Easier
Features media Yes Number of Conductors 1 Tip Size 1000 ft. Spool Dimensions and Weight Length Length 1000 Descriptions Excription Description THHN 600 STR BLACK 1000' extra long description SWC 32147106 THHN 600 Str Cu SIM Bk Long Description 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. Special Features Special Features No Lube Manufacturer Information Brand GTIN 00032886234460 UPC 032886234460 UPC 032886234460 Taxonomies, Classifications, and Categories Category Description BUILDING WIRE Type THHN-2 Availability minimum qty minimum qty 1000	Weight per unit	2.0 (lbs/ft)
mediaYesNumber of Conductors1Tip Size1000 ft. SpoolDimensions and WeightLength1000DescriptionsDescriptionTHHN 600 STR BLACK 1000'extra long descriptionSWC 32147106 THHN 600 Str Cu SIM BkLong Description600 Volts. Copper Conductor. Thermoplastic Insulation/NylonSheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling.Special FeaturesNo LubeManufacturer InformationEast GTIN UPCBrandCopper GTIN UPCCategory DescriptionBUILDING WIRE TypeTypeTHHN-2Availability minimum qty1000Packaging Carton1000	Product Category	THHN-T90-STR (Stranded)
Number of Conductors 1 Tip Size 1000 ft. Spool Dimensions and Weight 1000 Length 1000 Descriptions 1 Pescription THHN 600 STR BLACK 1000' extra long description SWC 32147106 THHN 600 Str Cu SIM Bk Long Description 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. Special Features No Lube Manufacturer Information Copper GTIN 00032886234460 UPC 032886234460 UPC 032886234460 Taxonomies, Classifications, and Categories Category Description BUILDING WIRE Type THHN-2 Availability 1000 minimum qty 1000	Features	
Tip Size 1000 ft. Spool Dimensions and Weight Length 1000 Descriptions 1000 pescription THHN 600 STR BLACK 1000' extra long description SWC 32147106 THHN 600 Str Cu SIM Bk Long Description 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. Special Features No Lube Manufacturer Information Easter Brand Copper GTIN 00032886234460 UPC 032886234460 Taxonomies, Classifications, and Categories Category Description BUILDING WIRE Type THHN-2 Availability 1000 Packaging Carton Carton 1000	media	Yes
Dimensions and Weight 1000 Length 1000 Descriptions THHN 600 STR BLACK 1000' extra long description SWC 32147106 THHN 600 Str Cu SIM Bk Long Description 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. Special Features No Lube Manufacturer Information East Brand Copper GTIN 00032886234460 UPC 032886234460 UPC 032886234460 Taxonomies, Classifications, and Categories Category Description Gategory Description BUILDING WIRE Type THHN-2 Availability minimum qty minimum qty 1000	Number of Conductors	
Length1000DescriptionsTHHN 600 STR BLACK 1000'extra long descriptionSWC 32147106 THHN 600 Str Cu SIM BkLong Description600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling.Special FeaturesNo LubeManufacturer Information BrandCopper GTIN 00032886234460 UPCTaxonomies, Classifications, and Categories Category DescriptionBUILDING WIRE THHN-2Availability minimum qty1000Packaging Carton1000	Tip Size	1000 ft. Spool
Length1000DescriptionsTHHN 600 STR BLACK 1000'extra long descriptionSWC 32147106 THHN 600 Str Cu SIM BkLong Description600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling.Special FeaturesNo LubeManufacturer Information BrandCopper GTIN 00032886234460 UPCTaxonomies, Classifications, and Categories Category DescriptionBUILDING WIRE THHN-2Availability minimum qty1000Packaging Carton1000	Dimensions and Weight	
DescriptionTHHN 600 STR BLACK 1000'extra long descriptionSWC 32147106 THHN 600 Str Cu SIM BkLong Description600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling.Special FeaturesNo LubeManufacturer InformationCopper GTIN 00032886234460BrandCopper G32886234460UPC032886234460UPC032886234460Taxonomies, Classifications, and Categories Category DescriptionBUILDING WIRE THHN-2Availability minimum qty1000Packaging Carton1000	•	1000
DescriptionTHHN 600 STR BLACK 1000'extra long descriptionSWC 32147106 THHN 600 Str Cu SIM BkLong Description600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling.Special FeaturesNo LubeManufacturer InformationCopper GTIN 00032886234460BrandCopper G32886234460UPC032886234460UPC032886234460Taxonomies, Classifications, and Categories Category DescriptionBUILDING WIRE THHN-2Availability minimum qty1000Packaging Carton1000	Descriptions	
extra long descriptionSWC 32147106 THHN 600 Str Cu SIM BkLong Description600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling.Special FeaturesNo LubeManufacturer InformationCopper GTIN 00032886234460BrandCopper G32886234460UPC032886234460UPC032886234460Taxonomies, Classifications, and Categories Category DescriptionBUILDING WIRE THHN-2Availability minimum qty1000Packaging Carton1000	-	THHN 600 STR BLACK 1000'
Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. Special Features Manufacturer Information Brand Copper GTIN 00032886234460 UPC 032886234460 Taxonomies, Classifications, and Categories Category Description BUILDING WIRE Type THHN-2 Availability 1000 Packaging 1000	-	SWC 32147106 THHN 600 Str Cu SIM Bk
Special FeaturesNo LubeManufacturer InformationBrandCopperGTIN00032886234460UPC032886234460Taxonomies, Classifications, and CategoriesCategory DescriptionBUILDING WIRETypeTHHN-2AvailabilityInterventionminimum qty1000Packaging CartonCarton1000	Long Description	Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier
Manufacturer InformationBrandCopperGTIN00032886234460UPC032886234460Taxonomies, Classifications, and CategoriesCategory DescriptionBUILDING WIRETypeTHHN-2AvailabilityInonominimum qty1000PackagingCarton1000	Special Features	5
BrandCopperGTIN00032886234460UPC032886234460Taxonomies, Classifications, and CategoriesCategory DescriptionBUILDING WIRETypeTHHN-2AvailabilityIndoominimum qty1000PackagingCarton1000		
GTIN00032886234460UPC032886234460Taxonomies, Classifications, and CategoriesCategory DescriptionBUILDING WIRETypeTHHN-2Availability minimum qty1000Packaging CartonCarton1000		Copper
Taxonomies, Classifications, and CategoriesCategory DescriptionBUILDING WIRETypeTHHN-2Availability1000Packaging1000Carton1000	GTIN	
Category DescriptionBUILDING WIRETypeTHHN-2Availability minimum qty1000Packaging Carton1000	UPC	032886234460
Category DescriptionBUILDING WIRETypeTHHN-2Availability minimum qty1000Packaging Carton1000	Taxonomies, Classifications, and	Categories
Type THHN-2 Availability minimum qty 1000 Packaging Carton 1000		-
minimum qty 1000 Packaging Carton 1000		THHN-2
minimum qty 1000 Packaging Carton 1000	Availability	
Carton 1000	5	1000
Carton 1000	1 3	
		1000
	Weight Per foot	