

## Deluxe Cord Grips

Aluminum Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables.

### IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages X-61 through X-68.

### Straight Male Thread



| NPT Thread Size Inches | Grip Diameter Range Inches (cm) | Form Size | Catalog Number |
|------------------------|---------------------------------|-----------|----------------|
| 3/8                    | .250"-.312" (.63-.79)           | F1        | 07401001       |
|                        | .312"-.375" (.79-.95)           |           | 07401002       |
|                        | .375"-.437" (.95-1.11)          |           | 07401003       |
| 1/2                    | .187"-.250" (.47-.63)           | F2        | 07401004       |
|                        | .250"-.375" (.63-.95)           |           | 07401006       |
|                        | .375"-.500" (.95-1.27)          |           | 07401008       |
| 1/2                    | .500"-.625" (1.27-1.59)         | F3        | 07401010       |
|                        | .625"-.750" (1.59-1.90)         |           | 074011247*     |
|                        | .750"-.875" (1.90-2.22)         |           | 074011248*     |
| 3/4                    | .187"-.250" (.47-.63)           | F2        | 07401011       |
|                        | .250"-.375" (.63-.95)           |           | 07401013       |
|                        | .375"-.500" (.95-1.27)          |           | 07401015       |
| 3/4                    | .500"-.625" (1.27-1.59)         | F3        | 07401017       |
|                        | .625"-.750" (1.59-1.90)         |           | 07401018       |
|                        | .750"-.875" (1.90-2.22)         |           | 074011249*     |
| 1                      | .375"-.500" (.95-1.27)          | F4        | 074011195      |
|                        | .500"-.625" (1.27-1.59)         |           | 07401019       |
|                        | .625"-.750" (1.59-1.90)         |           | 07401021       |
| 1                      | .750"-.875" (1.90-2.22)         | F5        | 07401023       |
|                        | .875"-.1.000" (2.22-2.54)       |           | 07401025       |
|                        | 1.000"-.1.125" (2.54-2.86)      |           | 074011250*     |
| 1                      | 1.125"-.1.250" (2.86-3.17)      | F5        | 074011028*     |
|                        | 1.250"-.1.375" (3.17-3.49)      |           | 074011029*     |
|                        | .750"-.875" (1.90-2.22)         |           | 074011251      |
| 1 1/4                  | .875"-.1.000" (2.22-2.54)       | F5        | 07401026       |
|                        | 1.000"-.1.125" (2.54-2.86)      |           | 07401027       |
|                        | 1.125"-.1.250" (2.86-3.17)      |           | 07401028       |
| 1 1/2                  | 1.250"-.1.375" (3.17-3.49)      | F5        | 074011178*     |
|                        | .750"-.875" (1.90-2.22)         |           | 074011252      |
|                        | .875"-.1.000" (2.22-2.54)       |           | 07401029       |
| 1 1/2                  | 1.000"-.1.125" (2.54-2.86)      | F5        | 07401030       |
|                        | 1.125"-.1.250" (2.86-3.17)      |           | 07401031       |
|                        | 1.250"-.1.375" (3.17-3.49)      |           | 07401032       |
| 1 1/2                  | 1.312"-.1.437" (3.33-3.65)      | F6        | 074011253      |
|                        | 1.437"-.1.562" (3.65-3.97)      |           | 074011254*     |
|                        | 1.562"-.1.687" (3.97-4.28)      |           | 074011255*     |
| 1 1/2                  | 1.687"-.1.812" (4.28-4.60)      | F6        | 074011256*     |
|                        | 1.750"-.1.875" (4.44-4.76)      |           | 074011257*     |
|                        | 1.250"-.1.375" (3.17-3.49)      |           | 074011258      |
| 2                      | 1.312"-.1.437" (3.33-3.65)      | F6        | 074011259      |
|                        | 1.437"-.1.562" (3.65-3.97)      |           | 07401033       |
|                        | 1.562"-.1.687" (3.97-4.28)      |           | 07401034       |
| 2                      | 1.687"-.1.812" (4.28-4.60)      | F7        | 07401035       |
|                        | 1.750"-.1.875" (4.44-4.76)      |           | 074011260      |
|                        | 1.812"-.1.937" (4.60-4.92)      |           | 074011261      |
| 2                      | 1.937"-.2.062" (4.92-5.24)      | F7        | 074011262*     |
|                        | 2.062"-.2.187" (5.24-5.55)      |           | 074011263*     |
|                        | 2.187"-.2.312" (5.55-5.87)      |           | 074011264*     |
| 2 1/2                  | 2.312"-.2.437" (5.87-6.19)      | F7        | 074011265*     |
|                        | 1.688"-.1.812" (4.29-4.60)      |           | 074011030      |
|                        | 1.812"-.1.937" (4.60-4.92)      |           | 074011031      |
| 2 1/2                  | 1.937"-.2.062" (4.92-5.24)      | F7        | 074011032      |
|                        | 2.062"-.2.187" (5.24-5.55)      |           | 074011033      |
|                        | 2.187"-.2.312" (5.55-5.87)      |           | 074011034      |
| 3                      | 2.312"-.2.437" (5.87-6.19)      | F7        | 074011266*     |
|                        | 1.937"-.2.062" (4.92-5.24)      |           | 074011036      |
|                        | 2.062"-.2.187" (5.24-5.55)      |           | 074011037      |
| 3                      | 2.187"-.2.312" (5.55-5.87)      | F8        | 074011038      |
|                        | 2.312"-.2.437" (5.87-6.19)      |           | 074011039      |
|                        | 2.437"-.2.625" (6.19-6.67)      |           | 074011186      |
| 3                      | 2.625"-.2.812" (6.67-7.14)      | F8        | 074011187      |
|                        | 2.812"-.3.000" (7.14-7.62)      |           | 074011188      |
|                        | 3.000"-.3.250" (7.62-8.25)      |           | 074011189*     |



Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).  
\*Cable jacket may have to be stripped to pass through connector body.

Dimensions in Inches (mm)

## Deluxe Cord Grips

Aluminum Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables.

### IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages X-61 through X-68.

### Straight Male Thread



| NPT Thread Size Inches | Grip Diameter Range Inches (cm) | Form Size | Catalog Number |
|------------------------|---------------------------------|-----------|----------------|
| 3/8                    | .250"-.312" (.63-.79)           | F1        | 07401001       |
|                        | .312"-.375" (.79-.95)           |           | 07401002       |
|                        | .375"-.437" (.95-1.11)          |           | 07401003       |
| 1/2                    | .187"-.250" (.47-.63)           | F2        | 07401004       |
|                        | .250"-.375" (.63-.95)           |           | 07401006       |
|                        | .375"-.500" (.95-1.27)          |           | 07401008       |
| 1/2                    | .500"-.625" (1.27-1.59)         | F3        | 07401010       |
|                        | .625"-.750" (1.59-1.90)         |           | 074011247*     |
|                        | .750"-.875" (1.90-2.22)         |           | 074011248*     |
| 3/4                    | .187"-.250" (.47-.63)           | F2        | 07401011       |
|                        | .250"-.375" (.63-.95)           |           | 07401013       |
|                        | .375"-.500" (.95-1.27)          |           | 07401015       |
| 3/4                    | .500"-.625" (1.27-1.59)         | F3        | 07401017       |
|                        | .625"-.750" (1.59-1.90)         |           | 07401018       |
|                        | .750"-.875" (1.90-2.22)         |           | 074011249*     |
| 1                      | .375"-.500" (.95-1.27)          | F4        | 074011195      |
|                        | .500"-.625" (1.27-1.59)         |           | 07401019       |
|                        | .625"-.750" (1.59-1.90)         |           | 07401021       |
| 1                      | .750"-.875" (1.90-2.22)         | F5        | 07401023       |
|                        | .875"-.1.000" (2.22-2.54)       |           | 07401025       |
|                        | 1.000"-.1.125" (2.54-2.86)      |           | 074011250*     |
| 1                      | 1.125"-.1.250" (2.86-3.17)      | F5        | 074011028*     |
|                        | 1.250"-.1.375" (3.17-3.49)      |           | 074011029*     |
|                        | .750"-.875" (1.90-2.22)         |           | 074011251      |
| 1 1/4                  | .875"-.1.000" (2.22-2.54)       | F5        | 07401026       |
|                        | 1.000"-.1.125" (2.54-2.86)      |           | 07401027       |
|                        | 1.125"-.1.250" (2.86-3.17)      |           | 07401028       |
| 1 1/2                  | 1.250"-.1.375" (3.17-3.49)      | F5        | 074011178*     |
|                        | .750"-.875" (1.90-2.22)         |           | 074011252      |
|                        | .875"-.1.000" (2.22-2.54)       |           | 07401029       |
| 1 1/2                  | 1.000"-.1.125" (2.54-2.86)      | F5        | 07401030       |
|                        | 1.125"-.1.250" (2.86-3.17)      |           | 07401031       |
|                        | 1.250"-.1.375" (3.17-3.49)      |           | 07401032       |
| 1 1/2                  | 1.312"-.1.437" (3.33-3.65)      | F6        | 074011253      |
|                        | 1.437"-.1.562" (3.65-3.97)      |           | 074011254*     |
|                        | 1.562"-.1.687" (3.97-4.28)      |           | 074011255*     |
| 1 1/2                  | 1.687"-.1.812" (4.28-4.60)      | F6        | 074011256*     |
|                        | 1.750"-.1.875" (4.44-4.76)      |           | 074011257*     |
|                        | 1.250"-.1.375" (3.17-3.49)      |           | 074011258      |
| 2                      | 1.312"-.1.437" (3.33-3.65)      | F6        | 074011259      |
|                        | 1.437"-.1.562" (3.65-3.97)      |           | 07401033       |
|                        | 1.562"-.1.687" (3.97-4.28)      |           | 07401034       |
| 2                      | 1.687"-.1.812" (4.28-4.60)      | F7        | 07401035       |
|                        | 1.750"-.1.875" (4.44-4.76)      |           | 074011260      |
|                        | 1.812"-.1.937" (4.60-4.92)      |           | 074011261      |
| 2                      | 1.937"-.2.062" (4.92-5.24)      | F7        | 074011262*     |
|                        | 2.062"-.2.187" (5.24-5.55)      |           | 074011263*     |
|                        | 2.187"-.2.312" (5.55-5.87)      |           | 074011264*     |
| 2 1/2                  | 2.312"-.2.437" (5.87-6.19)      | F7        | 074011265*     |
|                        | 1.688"-.1.812" (4.29-4.60)      |           | 074011030      |
|                        | 1.812"-.1.937" (4.60-4.92)      |           | 074011031      |
| 2 1/2                  | 1.937"-.2.062" (4.92-5.24)      | F7        | 074011032      |
|                        | 2.062"-.2.187" (5.24-5.55)      |           | 074011033      |
|                        | 2.187"-.2.312" (5.55-5.87)      |           | 074011034      |
| 3                      | 2.312"-.2.437" (5.87-6.19)      | F7        | 074011266*     |
|                        | 1.937"-.2.062" (4.92-5.24)      |           | 074011036      |
|                        | 2.062"-.2.187" (5.24-5.55)      |           | 074011037      |
| 3                      | 2.187"-.2.312" (5.55-5.87)      | F8        | 074011038      |
|                        | 2.312"-.2.437" (5.87-6.19)      |           | 074011039      |
|                        | 2.437"-.2.625" (6.19-6.67)      |           | 074011186      |
| 3                      | 2.625"-.2.812" (6.67-7.14)      | F8        | 074011187      |
|                        | 2.812"-.3.000" (7.14-7.62)      |           | 074011188      |
|                        | 3.000"-.3.250" (7.62-8.25)      |           | 074011189*     |

Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).  
\*Cable jacket may have to be stripped to pass through connector body.

Dimensions in Inches (mm)