

## **E**LLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**OELL2 3/4" Exprf Oell Cond Body & CVR** Crouse-Hinds

Catalog Number	0ELL2
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Oe Conduit Outlet Body With Cover, Feraloy Iron Alloy, LL Shape, 3/4"
Weight per unit	1.2 (lbs/each)
Product Category	Bodies & Covers
eatures	
connection	Threaded
dimensions	5.0000 IN X 2.0600 IN X 2.7500 IN
aterial, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
imensions and Weight	
Hub Size	1 in
escriptions	
Description	3/4" EXPRF OELL COND BODY & CVR
extra long description	CRS-H OELL2 3/4 CNDT OUTLET BODY CV
Features	OE and EKC conduit bodies from Eaton's Crouse-Hinds Division are installed in conduit systems within hazardous areas to protect conductors in threaded rigid conduit, provide an opening in the conduit system for pulling or splicing conductors, interconnect lengths of conduit, change direction of conduit, and provide access for maintenance and future system changes. OE and EKC conduit bodies are certified for use in Class I, Division 1 and Class II, Division 1 hazardous areas.
Long Description	Eaton Crouse-Hinds series Condulet OE conduit outlet body with cover, Feraloy iron alloy, LL shape, 3/4"
Product Type	3/4 CNDT Outlet Body CVR
Special Features	With Cover
anufacturer Information	
Brand	Eaton
GTIN	00782274552309
Manufacturers Part Number	OELL2
UPC	782274552309
axonomies, Classifications, and (	5
Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit outlet body with cover



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Packaging

Carton	1
Package	2
Weight Per each	1.16

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2
	Group F G, Class III
standard	UL 886, CSA C22.2