



**Open Switches**  
**T&B Catalog Number:**

OT30FT3  
 80432541552  
 Active

**UPC Number:**  
**Status:**  
**Description:**

3 pole, 30 amps rated at 600 VAC, UL 98, door mounted open non-fusible disconnect switch

**Features**

- Quick make, quick brake mechanism
- Extremely compact size
- Finger-proof construction with no hazardous exposed parts

**Application**

Suitable for use as motor disconnects or industrial control panel disconnects on service entrance equipment, panelboards, switchboards, industrial control equipment, motor control centers, etc.  
 Motor feeder applications and motor feeder short circuit and ground fault protection

**General**

Style	Door Mounted
Number of Poles	3
Series	Non-fusible

**Approvals**

UL Class	UL 98
----------	-------

**Dimension Information**

H x W x D (inches)	3.94 x 2.76 x .88
--------------------	-------------------

**Specifications**

Rated Current (Amps)	30
Rated Voltage AC	600

**Packaging**

T&B Inner Pack	1
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	0.97 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: techsupport@tnb.com



## Open Switches T&B Catalog Number:

**UPC Number:** OT30FT3  
**Status:** 80432541552  
**Description:** Active

3 pole, 30 amps rated at 600 VAC, UL 98, door mounted open non-fusible disconnect switch

### Features

- Quick make, quick brake mechanism
- Extremely compact size
- Finger-proof construction with no hazardous exposed parts

### Application

- Suitable for use as motor disconnects or industrial control panel disconnects on service entrance equipment, panelboards, switchboards, industrial control equipment, motor control centers, etc.
- Motor feeder applications and motor feeder short circuit and ground fault protection

### General

Style	Door Mounted
Number of Poles	3
Series	Non-fusible

### Approvals

UL Class	UL 98
----------	-------

### Dimension Information

H x W x D (inches)	3.94 x 2.76 x .88
--------------------	-------------------

### Specifications

Rated Current (Amps)	30
Rated Voltage AC	600

### Packaging

T&B Inner Pack	1
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	0.97 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: techsupport@tnb.com