

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



101048HSNK Wway 10X10X48 N1 HC

101048HSNK
Cooper B-Line/Cable Tray
Eaton B-Line Series Wireway, 10" Height, 48" Length, 10" Width, HSNK Wireway, Thru Holes, No Knockouts, Hinged Cover, Nema 1, Steel, Hinged, Ansi 61 Gray, 14 Gauge
34.7 (lbs/each)
Nema Type 1 Wireway & Fittings
HINGED
48.0000 IN X 10.0000 IN X 10.0000 IN
14 GAUGE STEEL
48 In
Gray
10.00 ln
48.00 in
10.00 ln
WWAY 10X10X48 N1 HC
B-LINE 101048 HSNK HINGE SCREW CVR
Eaton's B-Line series wiring troughs provide reliable
environmental protection and are used to house runs of control and power cable in wiring, junction, pull, and termination
applications.
Eaton B-Line series wireway, 10" height, 48" length, 10" width,
HSNK wireway, Thru holes, No knockouts, Hinged cover, NEMA 1
Steel, Hinged, ANSI 61 gray, 14 gauge
Hinge Screw CVR Wireway, No Knockouts, 10X10X48
Eaton
00782051479287

Ma

Brand	Eaton
GTIN	00782051479287
Manufacturers Part Number	101048HSNK
UPC	782051479287

Taxonomies, Classifications, and Categories

Category Description	STEEL WIRE WAY JUNCTION BOXES
Туре	Wireway



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	34.71
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Power Distribution and ControlsInd Facilities & Factories - Facility: Safety and Security SystemsInd Facilities & Factories - Facility: Power Distribution and ControlInd Facilities & Factories - Facility: Lighting and Lighting ControlsInd Facilities & Factories - Facility: Critical PowerInd Facilities & Factories - Industrial Facilities/Factories - OtherCommercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures -
Enclosure	NEMA 1, IP30

UL Listed, CSA C22.2.