



| CAT# | A | B | C |
|--------|-------|------|-------|
| 561A | 1.5 | .858 | .380 |
| 561ADC | 2.016 | --- | 1.087 |



| CAT# | A | B (Min-Max) | C | SCREWS |
|-------|--------|-------------|-------|--------|
| 100/i | 1.740 | 0.43-0.72 | .370 | 2 |
| 101/i | 2.110 | 0.64-1.03 | .400 | 2 |
| 102/i | 2.400 | 0.76-1.15 | .400 | 2 |
| 103/i | 2.870 | 1.09-1.73 | .540 | 2 |
| 104/i | 4.000 | 1.34-1.97 | .640 | 2 |
| 105/i | 6.000 | 1.65-2.61 | .750 | 2 |
| 106/i | 6.000 | 1.54-2.54 | .740 | 2 |
| 107 | 7.187 | 2.45-2.98 | .875 | 4 |
| 108 | 7.875 | 2.93-3.45 | 1.031 | 4 |
| 109 | 9.400 | 3.28-3.95 | 1.031 | 4 |
| 110 | 10.200 | 3.68-4.43 | 1.031 | 4 |
| 100M | 1.750 | 0.78-0.95 | .440 | 2 |
| 101M | 1.750 | 0.78-0.95 | .440 | 2 |
| 102M | 1.810 | 0.91-1.02 | .440 | 2 |
| 103M | 2.060 | 1.25-1.38 | .560 | 2 |
| 104M | 2.810 | 1.41-1.63 | .560 | 2 |
| 105M | 3.810 | 1.75-2.00 | .560 | 2 |
| 106M | 4.750 | 2.19-2.44 | .690 | 2 |
| 107M | 6.250 | 2.75-3.00 | .880 | 4 |
| 108M | 7.250 | 3.25-3.50 | 1.000 | 4 |
| 109M | 10.250 | 3.70-4.16 | 1.250 | 4 |
| 110M | 13.000 | 4.11-4.56 | 1.250 | 4 |
| 101Mi | 1.750 | 0.78-0.95 | .440 | 2 |
| 102Mi | 1.810 | 0.91-1.02 | .440 | 2 |
| 103Mi | 2.060 | 1.25-1.38 | .560 | 2 |
| 104Mi | 2.810 | 1.41-1.63 | .560 | 2 |
| 105Mi | 3.810 | 1.75-2.00 | .560 | 2 |
| 106Mi | 4.750 | 2.19-2.44 | .690 | 2 |
| 107Mi | 6.250 | 2.75-3.00 | .880 | 4 |
| 108Mi | 7.250 | 3.25-3.50 | 1.000 | 4 |
| 109Mi | 10.250 | 3.70-4.16 | 1.250 | 4 |
| 110Mi | 13.000 | 4.11-4.56 | 1.250 | 4 |

DUPLEX CONNECTOR

90° ANGLE ZINC/MALLEABLE IRON

| TOPAZ CAT # | UPC# | BX-FLEX SIZE | KO SIZE | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------------|---------|----------|-----------|----------|
| 561A | 15341 | 3/8" | 1/2" | 25 | 250 | 37 |
| 561ADC | 86339 | 3/8" | 1/2" | 25 | 250 | 30 |

BX-FLEX CONNECTORS

SQUEEZE TYPE 90° ANGLE

ZINC DIE CAST

| TOPAZ CAT # | UPC# | CONDUIT SIZE | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------------|----------|-----------|----------|
| 100 | 10340 | 3/8" 1/2" KO | 50 | 500 | 45 |
| 101 | 10350 | 1/2" | 25 | 250 | 35 |
| 102 | 10360 | 3/4" | 10 | 100 | 20 |
| 103 | 10370 | 1" | 5 | 50 | 19 |
| 104 | 10380 | 1 1/4" | 10 | 40 | 20 |
| 105 | 10390 | 1 1/2" | — | 5 | 5 |
| 106 | 10400 | 2" | — | 5 | 6 |
| 107 | 10410 | 2 1/2" | — | 5 | 18 |
| 108 | 10420 | 3" | — | 2 | 9 |
| 109 | 10430 | 3 1/2" | — | 1 | 9 |
| 110 | 10440 | 4" | — | 1 | 10 |

INSULATED THROAT

| | | | | | |
|------|-------|--------------|----|-----|----|
| 100i | 10341 | 3/8" 1/2" KO | 50 | 500 | 45 |
| 101i | 10351 | 1/2" | 25 | 250 | 35 |
| 102i | 10361 | 3/4" | 10 | 100 | 20 |
| 103i | 10371 | 1" | 5 | 50 | 19 |
| 104i | 10381 | 1 1/4" | 10 | 40 | 20 |
| 105i | 10391 | 1 1/2" | — | 5 | 5 |
| 106i | 10401 | 2" | — | 5 | 6 |

MALLEABLE IRON

| | | | | | |
|------|-------|--------|----|-----|----|
| 100M | 85239 | 3/8" | 25 | 250 | 40 |
| 101M | 10510 | 1/2" | 25 | 250 | 40 |
| 102M | 10520 | 3/4" | 10 | 100 | 30 |
| 103M | 10530 | 1" | 5 | 50 | 30 |
| 104M | 10540 | 1 1/4" | — | 50 | 38 |
| 105M | 10550 | 1 1/2" | — | 5 | 5 |
| 106M | 10560 | 2" | — | 5 | 10 |
| 107M | 10570 | 2 1/2" | — | 5 | 16 |
| 108M | 10580 | 3" | — | 2 | 9 |
| 109M | 10590 | 3 1/2" | — | 1 | 14 |
| 110M | 10600 | 4" | — | 1 | 24 |

INSULATED THROAT

| | | | | | |
|-------|-------|--------|----|-----|------|
| 101Mi | 10511 | 1/2" | 25 | 250 | 16 |
| 102Mi | 10521 | 3/4" | 10 | 100 | 30 |
| 103Mi | 10531 | 1" | 5 | 50 | 60 |
| 104Mi | 10541 | 1 1/4" | 5 | 50 | 76 |
| 105Mi | 10551 | 1 1/2" | — | 5 | 100 |
| 106Mi | 10561 | 2" | — | 5 | 200 |
| 107Mi | 10571 | 2 1/2" | — | 5 | 320 |
| 108Mi | 10581 | 3" | — | 2 | 450 |
| 109Mi | 10591 | 3 1/2" | — | 1 | 1400 |
| 110Mi | 10601 | 4" | — | 1 | 2400 |





| CAT# | A | B | C |
|--------|-------|------|-------|
| 561A | 1.5 | .858 | .380 |
| 561ADC | 2.016 | --- | 1.087 |



| CAT# | A | B (Min-Max) | C | SCREWS |
|-------|--------|-------------|-------|--------|
| 100/i | 1.740 | 0.43-0.72 | .370 | 2 |
| 101/i | 2.110 | 0.64-1.03 | .400 | 2 |
| 102/i | 2.400 | 0.76-1.15 | .400 | 2 |
| 103/i | 2.870 | 1.09-1.73 | .540 | 2 |
| 104/i | 4.000 | 1.34-1.97 | .640 | 2 |
| 105/i | 6.000 | 1.65-2.61 | .750 | 2 |
| 106/i | 6.000 | 1.54-2.54 | .740 | 2 |
| 107 | 7.187 | 2.45-2.98 | .875 | 4 |
| 108 | 7.875 | 2.93-3.45 | 1.031 | 4 |
| 109 | 9.400 | 3.28-3.95 | 1.031 | 4 |
| 110 | 10.200 | 3.68-4.43 | 1.031 | 4 |
| 100M | 1.750 | 0.78-0.95 | .440 | 2 |
| 101M | 1.750 | 0.78-0.95 | .440 | 2 |
| 102M | 1.810 | 0.91-1.02 | .440 | 2 |
| 103M | 2.060 | 1.25-1.38 | .560 | 2 |
| 104M | 2.810 | 1.41-1.63 | .560 | 2 |
| 105M | 3.810 | 1.75-2.00 | .560 | 2 |
| 106M | 4.750 | 2.19-2.44 | .690 | 2 |
| 107M | 6.250 | 2.75-3.00 | .880 | 4 |
| 108M | 7.250 | 3.25-3.50 | 1.000 | 4 |
| 109M | 10.250 | 3.70-4.16 | 1.250 | 4 |
| 110M | 13.000 | 4.11-4.56 | 1.250 | 4 |
| 101Mi | 1.750 | 0.78-0.95 | .440 | 2 |
| 102Mi | 1.810 | 0.91-1.02 | .440 | 2 |
| 103Mi | 2.060 | 1.25-1.38 | .560 | 2 |
| 104Mi | 2.810 | 1.41-1.63 | .560 | 2 |
| 105Mi | 3.810 | 1.75-2.00 | .560 | 2 |
| 106Mi | 4.750 | 2.19-2.44 | .690 | 2 |
| 107Mi | 6.250 | 2.75-3.00 | .880 | 4 |
| 108Mi | 7.250 | 3.25-3.50 | 1.000 | 4 |
| 109Mi | 10.250 | 3.70-4.16 | 1.250 | 4 |
| 110Mi | 13.000 | 4.11-4.56 | 1.250 | 4 |

DUPLEX CONNECTOR

90° ANGLE ZINC/MALLEABLE IRON

| TOPAZ CAT # | UPC# | BX-FLEX SIZE | KO SIZE | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------------|---------|----------|-----------|----------|
| 561A | 15341 | 3/8" | 1/2" | 25 | 250 | 37 |
| 561ADC | 86339 | 3/8" | 1/2" | 25 | 250 | 30 |

BX-FLEX CONNECTORS

SQUEEZE TYPE 90° ANGLE

ZINC DIE CAST

| TOPAZ CAT # | UPC# | CONDUIT SIZE | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------------|----------|-----------|----------|
| 100 | 10340 | 3/8" 1/2" KO | 50 | 500 | 45 |
| 101 | 10350 | 1/2" | 25 | 250 | 35 |
| 102 | 10360 | 3/4" | 10 | 100 | 20 |
| 103 | 10370 | 1" | 5 | 50 | 19 |
| 104 | 10380 | 1 1/4" | 10 | 40 | 20 |
| 105 | 10390 | 1 1/2" | — | 5 | 5 |
| 106 | 10400 | 2" | — | 5 | 6 |
| 107 | 10410 | 2 1/2" | — | 5 | 18 |
| 108 | 10420 | 3" | — | 2 | 9 |
| 109 | 10430 | 3 1/2" | — | 1 | 9 |
| 110 | 10440 | 4" | — | 1 | 10 |

INSULATED THROAT

| | | | | | |
|------|-------|--------------|----|-----|----|
| 100i | 10341 | 3/8" 1/2" KO | 50 | 500 | 45 |
| 101i | 10351 | 1/2" | 25 | 250 | 35 |
| 102i | 10361 | 3/4" | 10 | 100 | 20 |
| 103i | 10371 | 1" | 5 | 50 | 19 |
| 104i | 10381 | 1 1/4" | 10 | 40 | 20 |
| 105i | 10391 | 1 1/2" | — | 5 | 5 |
| 106i | 10401 | 2" | — | 5 | 6 |

MALLEABLE IRON

| | | | | | |
|------|-------|--------|----|-----|----|
| 100M | 85239 | 3/8" | 25 | 250 | 40 |
| 101M | 10510 | 1/2" | 25 | 250 | 40 |
| 102M | 10520 | 3/4" | 10 | 100 | 30 |
| 103M | 10530 | 1" | 5 | 50 | 30 |
| 104M | 10540 | 1 1/4" | — | 50 | 38 |
| 105M | 10550 | 1 1/2" | — | 5 | 5 |
| 106M | 10560 | 2" | — | 5 | 10 |
| 107M | 10570 | 2 1/2" | — | 5 | 16 |
| 108M | 10580 | 3" | — | 2 | 9 |
| 109M | 10590 | 3 1/2" | — | 1 | 14 |
| 110M | 10600 | 4" | — | 1 | 24 |

INSULATED THROAT

| | | | | | |
|-------|-------|--------|----|-----|------|
| 101Mi | 10511 | 1/2" | 25 | 250 | 16 |
| 102Mi | 10521 | 3/4" | 10 | 100 | 30 |
| 103Mi | 10531 | 1" | 5 | 50 | 60 |
| 104Mi | 10541 | 1 1/4" | 5 | 50 | 76 |
| 105Mi | 10551 | 1 1/2" | — | 5 | 100 |
| 106Mi | 10561 | 2" | — | 5 | 200 |
| 107Mi | 10571 | 2 1/2" | — | 5 | 320 |
| 108Mi | 10581 | 3" | — | 2 | 450 |
| 109Mi | 10591 | 3 1/2" | — | 1 | 1400 |
| 110Mi | 10601 | 4" | — | 1 | 2400 |

