

Electrical Construction Supplies

Pipe Mounting Wireholders

Designed especially for service entrance masts. May be used in other applications requiring insulator attachment to pipe. All ferrous metal parts are hot dipped galvanized. Assembly of parts after galvanizing assures all surfaces are protected from rust and corrosion.



| Catalog No. | Style | Pipe Size (inches) | Std. Pkg. | Wt. per 100 |
|-------------|------------------------|--------------------|-----------|-------------|
| 6316 | 1986 | 1 1/4 - 1 1/2 | 50 | 94 |
| 6416 | 1986 | 2 | 50 | 94 |
| 6516 | 1986 | 2 1/2 | 50 | 100 |
| 6912 | "Universal" Reinforced | 1 1/4 - 2 1/2 | 25 | 168 |
| 6913 | "Universal" Reinforced | 3" - 4 | 10 | 175 |
| 6402 | Triplex Hanger | 2 | 50 | 40 |

Clevises

Clevises are suitable for dead-ending service drops at either end and for general use in commercial and industrial applications. All steel components are hot dipped galvanized in accordance with the latest applicable ASTM specifications. Clevis and insulator are completely assembled and packed in convenient standard package quantities.



| Catalog No. | Insulators Hole | Extension (inches) | Mounting (inches) | Steel Size (inches) | Std. Pkg. | Wt. per 100 |
|-------------|-----------------|--------------------|-------------------|---------------------|-----------|-------------|
| 4170 | 5107 | 6 1/2 | 11/16 | 3/16 x 3/4 | 25 | 132 |
| 4172 | 5107 | 4 | 11/16 | 3/16 x 1 1/2 | 25 | 152 |
| 4111 | 5101 | 4 | 11/16 Sqr. | 1/8 x 1/2 x 1 | 10 | 250 |
| 4112 | 5101 | 4 | 11/16 x 7/8 | 3/16 x 3 | 10 | 360 |
| 4113 | 5101 | 5 | 3/4 | 1/8 x 1 3/4 | 10 | 260 |
| 4115 | 5116 | 5 3/4 | 11/16 x 25/32 | 1/4 x 1 1/2 | 5 | 520 |

Wedge Grip Clamps

These clamps can be installed at any point on the conductor, allowing for sag before the conductor is cut. Made with aluminum wedge and shell with stainless steel solid bail or nylon jacketed galvanized steel aircraft strand flexible bail.

Solid-1061



Flexible-1061F



| Catalog No. | Bail Type | Conductor Size | | Bail Length (inches) | Std. Pkg | Wt. per 100 |
|-------------|-----------|----------------|-----------|----------------------|----------|-------------|
| | | Min. ACSR | Max. ACSR | | | |
| 1061 | Solid | 6 | 2 | 6 1/2 | 50 | 15 |
| 1062 | Solid | 4 | 1/0 | 6 1/2 | 25 | 26 |
| 1063 | Solid | 2/0 | 4/0 | 6 1/2 | 25 | 33 |
| 1061F | Flexible | 6 | 2 | 12 | 50 | 16 |
| 1062F | Flexible | 4 | 1/0 | 14 | 25 | 28 |
| 1063F | Flexible | 2/0 | 4/0 | 14 | 25 | 36 |

Electrical Construction Supplies

Pipe Mounting Wireholders

Designed especially for service entrance masts. May be used in other applications requiring insulator attachment to pipe. All ferrous metal parts are hot dipped galvanized. Assembly of parts after galvanizing assures all surfaces are protected from rust and corrosion.



| Catalog No. | Style | Pipe Size (inches) | Std. Pkg. | Wt. per 100 |
|-------------|------------------------|--------------------|-----------|-------------|
| 6316 | 1986 | 1 1/4 - 1 1/2 | 50 | 94 |
| 6416 | 1986 | 2 | 50 | 94 |
| 6516 | 1986 | 2 1/2 | 50 | 100 |
| 6912 | "Universal" Reinforced | 1 1/4 - 2 1/2 | 25 | 168 |
| 6913 | "Universal" Reinforced | 3" - 4 | 10 | 175 |
| 6402 | Triplex Hanger | 2 | 50 | 40 |

Clevises

Clevises are suitable for dead-ending service drops at either end and for general use in commercial and industrial applications. All steel components are hot dipped galvanized in accordance with the latest applicable ASTM specifications. Clevis and insulator are completely assembled and packed in convenient standard package quantities.



| Catalog No. | Insulators Hole | Extension (inches) | Mounting (inches) | Steel Size (inches) | Std. Pkg. | Wt. per 100 |
|-------------|-----------------|--------------------|-------------------|---------------------|-----------|-------------|
| 4170 | 5107 | 6 1/2 | 11/16 | 3/16 x 3/4 | 25 | 132 |
| 4172 | 5107 | 4 | 11/16 | 3/16 x 1 1/2 | 25 | 152 |
| 4111 | 5101 | 4 | 11/16 Sqr. | 1/8 x 1/2 x 1 | 10 | 250 |
| 4112 | 5101 | 4 | 11/16 x 7/8 | 3/16 x 3 | 10 | 360 |
| 4113 | 5101 | 5 | 3/4 | 1/8 x 1 3/4 | 10 | 260 |
| 4115 | 5116 | 5 3/4 | 11/16 x 25/32 | 1/4 x 1 1/2 | 5 | 520 |

Wedge Grip Clamps

These clamps can be installed at any point on the conductor, allowing for sag before the conductor is cut. Made with aluminum wedge and shell with stainless steel solid bail or nylon jacketed galvanized steel aircraft strand flexible bail.



| Catalog No. | Bail Type | Conductor Size | | Bail Length (inches) | Std. Pkg | Wt. per 100 |
|-------------|-----------|----------------|-----------|----------------------|----------|-------------|
| | | Min. ACSR | Max. ACSR | | | |
| 1061 | Solid | 6 | 2 | 6 1/2 | 50 | 15 |
| 1062 | Solid | 4 | 1/0 | 6 1/2 | 25 | 26 |
| 1063 | Solid | 2/0 | 4/0 | 6 1/2 | 25 | 33 |
| 1061F | Flexible | 6 | 2 | 12 | 50 | 16 |
| 1062F | Flexible | 4 | 1/0 | 14 | 25 | 28 |
| 1063F | Flexible | 2/0 | 4/0 | 14 | 25 | 36 |