



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



1086SDF Encl 11.42X9.79X6.31 N4X FG HNG SC

Cooper B-Line/Cable Tray

Catalog Number	1086SDF
Manufacturer	Cooper B-Line/Cable Tray
Description	Eaton B-Line Series Premier Fiberglass Enclosure, 11.42"Height, 6.31"Length, 9.79"Width, Nema 4X, Hinged Cover, SDF Enclosure, Wall Mount, Medium Single Door, Optional External Mounting Feet, Fiberglass, Seamless Poured In-Place Gasket
Weight per unit	4.5 (lbs/each)
Product Category	Nema Types 4X & 6

Features

dimensions	6.3100 IN X 9.7900 IN X 11.4200 IN
Mounting Type	Wall

Material, Color, and Finish

Color	Gray
-------	------

Dimensions and Weight

Size	8.00 In Width X 6.00 In Depth X 10.00 In Height
------	---

Descriptions

Construction	Impact Resistant, Non-Conductive, Light-Weight
Description	ENCL 11.42X9.79X6.31 N4X FG HNG SC
extra long description	B-LINE 1086-SDF TYPE 4X FIBERGLASS
Features	Eaton's B-Line series Type 4X Premier series fiberglass enclosures are designed to house electrical and electronic controls and instruments to help protect against corrosion, windblown dust and rain, splashing water, and hose directed water.
Long Description	Eaton B-Line series Premier fiberglass enclosure, 11.42"height, 6.31"length, 9.79"width, NEMA 4X, Hinged cover, SDF enclosure, Wall mount, Medium single door, Optional external mounting feet, Fiberglass, Seamless poured in-place gasket

Product Type	Type 4X Fiberglass Premier Screw CVR Enc, 10X8X6
Special Features	Stainless screws

Manufacturer Information

Brand	Eaton
GTIN	00782051524185
Manufacturers Part Number	1086-SDF
UPC	782051524185

Taxonomies, Classifications, and Categories

Category Description	VYNCKIER FIBERGLASS ENCLOSURES
Type	Fiberglass enclosures



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	4.5

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Power Distribution and Controls Commercial / Institutional Buildings / Structures - Critical Power Ind Facilities & Factories - Facility: Safety and Security Systems Ind Facilities & Factories - Facility: Critical Power Ind Facilities & Factories - Facility: Automation and Monitoring Ind Facilities & Factories - Industrial Facilities/Factories - Other Commercial / Institutional Buildings / Structures - Lighting and Lighting Controls Ind Facilities & Factories -
nema rating standard	4X UL 50, NEMA, Not Applicable