



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 10RC8FLE 12-10 Fork Terminal

*Abb Installation Products, Inc*

|                  |   |
|------------------|---|
| Catalog Number   | 10RC8FLE  |
| Manufacturer     | Abb Installation Products, Inc  |
| Description      | Fork Terminal, #12 Awg Conductor Size, #10 Awg Conductor Size, Insulated, Vinyl Insulation Material, Copper Conductor Material, Yellow Insulation Color, 600 V Ac, 1.09 In Overall Length, 0.220 In Insulation Length, 0.006 LB |
| Weight per unit  | 0.0060 (lbs/each)   |
| Product Category | Small Terminals & Connectors  |

### Features

|           |           |
|-----------|-----------|
| Material  | Copper    |
| Wire Size | 12-10 AWG |

### Material, Color, and Finish

|       |        |
|-------|--------|
| Color | Yellow |
|-------|--------|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | 12-10 FORK TERMINAL  |
| extra long description | ABB 10RC-8FL INS VINYL LKG FORK TER  |
| Special Features       | Locking fork terminals have a specially designed tongue that lets them go on like a fork and stay on like a ring |

### Manufacturer Information

|       |                |
|-------|----------------|
| Brand | Sta-Kon        |
| GTIN  | 00786210807249 |
| UPC   | 786210807249   |

### Taxonomies, Classifications, and Categories

|                      |                                       |
|----------------------|---------------------------------------|
| Category Description | TERMINALS                             |
| Type                 | Vinyl Insulated Locking Fork Terminal |

### Availability

|             |          |
|-------------|----------|
| minimum qty | 50       |
| Status      | Inactive |

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 500   |
| Package         | 5000  |
| Weight Per each | 0.006 |

### Uses, Certifications, and Standards

|          |          |
|----------|----------|
| standard | UL E9809 |
|----------|----------|