



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 14RB250T 16-14 Male Disconnect

*Abb Installation Products, Inc*

|                  |   |
|------------------|---|
| Catalog Number   | 14RB250T  |
| Manufacturer     | Abb Installation Products, Inc  |
| Description      | Vinyl Insulated Male Tab, Length .95 Inches, Maximum Insulated .170, Tab Size .250X.032, Wire Range #16-#14 Awg, Color Blue, Copper, Tin Plated |
| Weight per unit  | 0.0029 (lbs/each)   |
| Product Category | Small Terminals & Connectors  |

### Features

|            |       |
|------------|-------|
| insulation | Vinyl |
| Material   | Brass |

### Material, Color, and Finish

|        |            |
|--------|------------|
| Color  | Blue       |
| Finish | Tin Plated |

### Descriptions

|                        |   |
|------------------------|---|
| Description            | 16-14 MALE DISCONNECT   |
| extra long description | ABB 14RB-250T INS VINYL MALE-250 TA   |
| Long Description       | Vinyl Insulated Male Tab, Length .95 Inches, Maximum Insulated .170, Tab Size .250x.032, Wire Range #16-#14 AWG, Color Blue, Copper, Tin Plated |
| Product Type           | Ins Vinyl Male-250 Tab 16-14 Blue   |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | Sta-Kon        |
| GTIN                      | 00786210800783 |
| Manufacturers Part Number | 14RB-250T      |
| UPC                       | 786210800783   |

### Taxonomies, Classifications, and Categories

|                      |                                 |
|----------------------|---------------------------------|
| Category Description | TERMINALS                       |
| Type                 | Vinyl Insulated Male Disconnect |

### Packaging

|                 |        |
|-----------------|--------|
| Carton          | 100    |
| Weight Per each | 0.0029 |

### Uses, Certifications, and Standards

|          |           |
|----------|-----------|
| standard | UL E66716 |
|----------|-----------|