

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





#### 1597TRAI Radiant Self Test TR Alrm Gfci 15A 125V Iv

Pass & Seymour/Legrand

Catalog Number	1597TRAI
Manufacturer	Pass & Seymour/Legrand
Description	15A 125V Gfci Tamper Resistant Receptacle, Ivory
Weight per unit	0.2750 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro

#### **Features**

actuator	Control Circuit
amperage rating	15
connection	Back and side wire
interrupt rating	4 to 6 mA
Material	Thermoplatic
Poles	2
trip range	4 to 6 mA
Trip Type	.025 Second Nominal
Voltage Rating	125

#### **Dimensions and Weight**

Height	4.2
Length	1.03
Width	1.73

### **Descriptions**

Description	RADIANT SELF TEST TR ALRM GFCI 15A 125V IV
extra long description	P&S 1597TRAI RADIANT SLF TST TR ALR
Long Description	15A 125V GFCI Tamper Resistant Receptacle, Ivory
Product Type	Radiant SLF TST TR Alrm Gfci 15A 125V I
Special Features	Pass & Seymour invented the GFCI receptacle, and at Legrand, we're constantly reinventing it to ensure the highest level of safety possible. From the most advanced self-testing device to audible alarms to nightlight combos, we're continuously resetting the bar on GFCI innovation and safety.

#### **Manufacturer Information**

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007048421
Manufacturers Part Number	1597-TRAI
UPC	785007048421

### **Taxonomies, Classifications, and Categories**

Category Description	Residential GFCI devices
Type	Specification Grade Tamper-Resistant 15A Self-Test Duplex GFCI



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging
-----------

Carton	1	
Package	10	
Weight Per each	0.275	

## Uses, Certifications, and Standards

Application	Commercial/Residential
environmental conditions	95% Humidity, UL 94 V2
Frequency Rating	60 Hz
Operating Temperature	-35°C to +66°C
standard	cULus, UL Listed, FSUL