


## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service





### **167G 2-1/2" Grounding Locknut Diecast** *Nsi Industries*

Catalog Number	167G
Manufacturer	Nsi Industries
Description	Locknut, Grounding, Zinc Die Cast, Size 2-1/2 Inch, 14-1/0 Lug
Weight per unit	0.4690 (lbs/each)
Product Category	Grounding & Bonding Equipment

#### **Features**

Cable Entry	Through the fitting or conduit that the locknut is attached to
Material	Zinc Die Cast, Tin Plated Aluminum
modia	Voc

#### Material, Color, and Finish

Color	Gray	
Finish	Ball burnish	

#### **Dimensions and Weight**

Size 2-1/2	
------------	--

#### **Descriptions**

Description	2-1/2" GROUNDING LOCKNUT DIECAST
extra long description	BPT 167-G 2-1/2" GROUNDING L/N W/LU
Features	Problem Solver: Connect and Ground with just a locknut!
Long Description	Locknut, Grounding, Zinc Die Cast, Size 2-1/2 Inch, 14-1/0 Lug
Product Type	2-1/2" Grounding L/N W/Lug
Special Features	Bridgeport's grounding locknuts provide a secure connection to the enclosure, and 3 tapped holes for proper placement of the ground lug.

#### **Manufacturer Information**

Brand	Bridgeport Fittings
GTIN	00781747901675
Manufacturers Part Number	167G
UPC	781747901675

#### **Taxonomies, Classifications, and Categories**

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding
	Fittings & Ground Rods
Туре	LOCKNUT

#### **Trade Size**

Trade Size 2	2,5
--------------	-----



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	5
Package	25
Weight Per each	0.469
Uses, Certifications, and Standards	
Application	Used in place where a grounding bushing and locknut, for bonding connectors inside the box. Perfect for tight locations or fittings with shorter locknut threads. ETL Listed for use with all Bridgeport Fittings connectors.
standard	Listed ETL Conforms to UL STD 514B Certified to CAN/CSA STD.

C22.2 No. 18.3