

# Rigid/Intermediate Grade Conduit Fittings

## Conduit Couplings

### THREE-PIECE CONDUIT COUPLINGS – MALLEABLE IRON

#### Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

#### Features:

- NPSM threads

#### Standard Materials:

- Heavy duty casting
- Malleable iron

#### Standard Finish:

- Zinc plated

#### Options:

##### Description

- Hot dip galvanized .....**Suffix HDG**

#### Malleable Iron (Concrete Tight)

UL File No. E-19189



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
<b>190M</b>	1/2"	25	23
<b>191</b>	3/4"	25	35
<b>192</b>	1"	10	60
<b>193</b>	1 1/4"	5	91
<b>194</b>	1 1/2"	5	167
<b>195</b>	2"	5	215
<b>196</b>	2 1/2"	2	430
<b>197</b>	3"	1	463
<b>198</b>	3 1/2"	1	655
<b>199</b>	4"	1	800
<b>188†</b>	5"	1	1200
<b>189†</b>	6"	1	2100

†Not UL Listed.

### NO DISASSEMBLY RAIN-TIGHT THREE-PIECE CONDUIT COUPLINGS – STEEL

#### Applications:

- Used to join two lengths of rigid and IMC conduit together in applications where conduit cannot be turned
- Unique design allows for a quick and easy install which translates into labor savings when compared with traditional fittings

#### Features:

- Manufactured out of steel to provide mechanical protection and solid grounding of one conduit to another
- Zinc electroplated design which protects against corrosion in damp locations
- No disassembly design which allows for the pairing of two pieces of conduit without the hassle of taking apart the fitting; conduit is input on each end of the coupling and the locknut is tightened down to provide quick and easy raintight seal
- Neoprene rubber o-ring which prevents against the penetration of water or moisture
- RoHS compliant

#### Standard Materials:

- Body and gland nut – steel
- O-ring – neoprene rubber

#### Standard Finish:


- Zinc electroplated



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
<b>190RTQ</b>	1/2"	125	23
<b>191RTQ</b>	3/4"	100	29
<b>192RTQ</b>	1"	64	48
<b>193RTQ</b>	1 1/4"	48	65
<b>194RTQ</b>	1 1/2"	32	97
<b>195RTQ</b>	2"	24	138

#### Dimensions (in Inches):

Cat. #	A	B
<b>190RTQ</b>	1 1/16	1 5/8
<b>191RTQ</b>	1 11/16	1 9/16
<b>192RTQ</b>	1 3/4	1 15/16
<b>193RTQ</b>	1 3/4	2 5/16
<b>194RTQ</b>	1 13/16	2 13/16
<b>195RTQ</b>	2 1/16	3 5/16



# Rigid/Intermediate Grade Conduit Fittings

## Conduit Couplings

Rigid Fittings

### RIGID CONDUIT COUPLINGS – STEEL

#### Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

#### Standard Material:

- Galvanized steel

UL File No. E-25501



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
RC50	1/2"	10	12
RC75	3/4"	10	18
RC100	1"	10	29
RC125	1 1/2"	5	38
RC150	1 1/2"	5	52
RC200	2"	5	69
RC250	2 1/2"	2	181
RC300	3"	1	220
RC350	3 1/2"	1	377
RC400	4"	1	298
RC500	5"	1	477
RC600	6"	1	684

### RIGID CONDUIT COUPLINGS – ALUMINUM

#### Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

#### Features:

- Lightweight
- Easy to install
- Corrosion-resistant

#### Standard Material:

- Aluminum

UL File No. E-324286



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
RC50SA	1/2"	50	6
RC75SA	3/4"	50	9
RC100SA	1"	50	13
RC125SA	1 1/4"	50	19
RC150SA	1 1/2"	50	23
RC200SA	2"	20	35
RC250SA	2 1/2"	12	68
RC300SA	3"	12	91
RC350SA	3 1/2"	12	108
RC400SA	4"	12	142
RC500SA	5"	1	242
RC600SA	6"	1	320

# Rigid/Intermediate Grade Conduit Fittings

## Conduit Couplings

### THREE-PIECE CONDUIT COUPLINGS – MALLEABLE IRON

#### Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

#### Features:

- NPSM threads

#### Standard Materials:

- Heavy duty casting
- Malleable iron

#### Standard Finish:

- Zinc plated

#### Options:

##### Description

- Hot dip galvanized .....**Suffix HDG**

#### Malleable Iron (Concrete Tight)

UL File No. E-19189



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
<b>190M</b>	1/2"	25	23
<b>191</b>	3/4"	25	35
<b>192</b>	1"	10	60
<b>193</b>	1 1/4"	5	91
<b>194</b>	1 1/2"	5	167
<b>195</b>	2"	5	215
<b>196</b>	2 1/2"	2	430
<b>197</b>	3"	1	463
<b>198</b>	3 1/2"	1	655
<b>199</b>	4"	1	800
<b>188†</b>	5"	1	1200
<b>189†</b>	6"	1	2100

†Not UL Listed.

### NO DISASSEMBLY RAIN-TIGHT THREE-PIECE CONDUIT COUPLINGS – STEEL

#### Applications:

- Used to join two lengths of rigid and IMC conduit together in applications where conduit cannot be turned
- Unique design allows for a quick and easy install which translates into labor savings when compared with traditional fittings

#### Features:

- Manufactured out of steel to provide mechanical protection and solid grounding of one conduit to another
- Zinc electroplated design which protects against corrosion in damp locations
- No disassembly design which allows for the pairing of two pieces of conduit without the hassle of taking apart the fitting; conduit is input on each end of the coupling and the locknut is tightened down to provide quick and easy raintight seal
- Neoprene rubber o-ring which prevents against the penetration of water or moisture
- RoHS compliant

#### Standard Materials:

- Body and gland nut – steel
- O-ring – neoprene rubber

#### Standard Finish:


- Zinc electroplated



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
<b>190RTQ</b>	1/2"	125	23
<b>191RTQ</b>	3/4"	100	29
<b>192RTQ</b>	1"	64	48
<b>193RTQ</b>	1 1/4"	48	65
<b>194RTQ</b>	1 1/2"	32	97
<b>195RTQ</b>	2"	24	138

#### Dimensions (in Inches):

Cat. #	A	B
<b>190RTQ</b>	1 1/16	1 5/8
<b>191RTQ</b>	1 11/16	1 9/16
<b>192RTQ</b>	1 3/4	1 15/16
<b>193RTQ</b>	1 3/4	2 5/16
<b>194RTQ</b>	1 13/16	2 13/16
<b>195RTQ</b>	2 1/16	3 5/16



# Rigid/Intermediate Grade Conduit Fittings

## Conduit Couplings

Rigid Fittings

### RIGID CONDUIT COUPLINGS – STEEL

#### Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

#### Standard Material:

- Galvanized steel

UL File No. E-25501



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
RC50	1/2"	10	12
RC75	3/4"	10	18
RC100	1"	10	29
RC125	1 1/2"	5	38
RC150	1 1/2"	5	52
RC200	2"	5	69
RC250	2 1/2"	2	181
RC300	3"	1	220
RC350	3 1/2"	1	377
RC400	4"	1	298
RC500	5"	1	477
RC600	6"	1	684

### RIGID CONDUIT COUPLINGS – ALUMINUM

#### Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

#### Features:

- Lightweight
- Easy to install
- Corrosion-resistant

#### Standard Material:

- Aluminum

UL File No. E-324286



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
RC50SA	1/2"	50	6
RC75SA	3/4"	50	9
RC100SA	1"	50	13
RC125SA	1 1/4"	50	19
RC150SA	1 1/2"	50	23
RC200SA	2"	20	35
RC250SA	2 1/2"	12	68
RC300SA	3"	12	91
RC350SA	3 1/2"	12	108
RC400SA	4"	12	142
RC500SA	5"	1	242
RC600SA	6"	1	320