



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



2160 Rac 2-1/2" Emt Inslted Set Screw Conn

Hubbell--Raco

| | |
|------------------|---|
| Catalog Number | 2160 |
| Manufacturer | Hubbell--Raco |
| Description | Set-Screw Connector, Insulated, Steel, 2-1/2 In. Trade Size |
| Weight per unit | 1.4 (lbs/each) |
| Product Category | Steel Insulated Straight Set S |

Features

| | |
|-------------------|------------|
| Conduit Type | EMT |
| fitting type | Connectors |
| installation type | Screw |
| Insulation Type | Insulated |
| pallet quantity | 1000 |
| Wall Thickness | 0.115 |

Material, Color, and Finish

| | |
|-------|--------|
| Color | Silver |
|-------|--------|

Dimensions and Weight

| | |
|--------|-------|
| Length | 2.875 |
|--------|-------|

Descriptions

| | |
|------------------------|--|
| Description | RAC 2-1/2" EMT INSLTED SET SCREW CONN |
| extra long description | RACO 2160 CONN RGD/EMT SET SCREW IN |
| Long Description | SET-SCREW CONNECTOR, INSULATED, STEEL, 2-1/2 IN. TRADE SIZE |
| Product Type | Commercial Fittings |
| Special Features | provides a concrete tight connection when taped;UL listed for use with Rigid/IMC conduit;zinc electro plated |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | RACO |
| GTIN | 00050169021606 |
| Manufacturers Part Number | 2160 |
| UPC | 050169021606 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------------|
| Category Description | STEEL EMT FITTINGS |
| Type | Set screw connector, insulated, EMT |

Trade Size

| | |
|------------|----------|
| Trade Size | 2-1/2 IN |
|------------|----------|



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|-------|
| Carton | 1 |
| Weight Per each | 1.402 |

Uses, Certifications, and Standards

| | |
|-------------|------------|
| Application | Electrical |
| standard | UL 514B |