



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 2800T Nsi 2-800T Aluminum Doubl

*Nsi Industries*

Catalog Number	2800T
Manufacturer	Nsi Industries
Description	2 Port Aluminum Lug 800 - 300 MCM Aluminum Double Lugs Are Versatile and Reuseable Set Screw Connectors Made Of 6061T-6 Aluminum Alloy. Electro Tin Plated For Low Contact Resistance. Suitable For Use With Both Copper and Aluminum Conductors. Rated 600 Volts, 90 Degrees C. UI 486A/B Listed.
Weight per unit	0.9000 (lbs/each)
Product Category	Large Terminals & Connectors

### Features

Warranty	1 YEAR
----------	--------

### Material, Color, and Finish

Color	Aluminum
Finish	Aluminum

### Descriptions

Description	NSI 2-800T ALUMINUM DOUBL
extra long description	NSI 2-800T Dual Ratd Lug Two 800-30
Features	2 Port Aluminum Lug 800 - 300 MCM Aluminum Double Lugs are versatile and reuseable set screw connectors made of 6061T-6 aluminum alloy. Electro tin plated for low contact resistance. Suitable for use with both copper and aluminum conductors. Rated 600 volts, 90 degrees C. UL 486A/B Listed.
Long Description	2 Port Aluminum Lug 800 - 300 MCM Aluminum Double Lugs are versatile and reuseable set screw connectors made of 6061T-6 aluminum alloy. Electro tin plated for low contact resistance. Suitable for use with both copper and aluminum conductors. Rated 600 volts, 90 degrees C. UL 486A/B Listed.
Product Type	Dual Ratd Lug Two 800-300
Special Features	(2) 800-300 MCM - Dual Rated - 2 Pack

### Manufacturer Information

Brand	Platinum Tools
GTIN	00662381001252
Manufacturers Part Number	2-800T
UPC	662381001252

### Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Aluminum Double Lug



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Package	2
Weight Per each	0.9

## Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	cULus