



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 30026 Noalox (4 Oz. Bottle)

*Ideal*

|                  |  |
|------------------|--|
| Catalog Number   | 30026  |
| Manufacturer     | Ideal  |
| Description      | Anti-Oxidant Compound, 4 Oz Squeeze Bottle, Petroleum Base, 1.04 Specific Gravity, 310 °F Flash Point, 0.33 LB |
| Weight per unit  | 0.3250 (lbs/each)  |
| Product Category | Paint, Chemicals, Etc.   |

### Features

|                  |      |
|------------------|------|
| specific gravity | 1.04 |
|------------------|------|

### Dimensions and Weight

|      |                     |
|------|---------------------|
| Size | 4 OZ Squeeze Bottle |
|------|---------------------|

### Descriptions

|             |                       |
|-------------|-----------------------|
| Description | NOALOX (4 OZ. BOTTLE) |
|-------------|-----------------------|

|                        |                                      |
|------------------------|--------------------------------------|
| extra long description | IDEAL 30-026 NOALOX (4 OZ CONTAINER) |
|------------------------|--------------------------------------|

|          |   |
|----------|---|
| Features | IDEAL Noalox Anti-Oxidant compound improves efficiency and service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts. It is used with all types of pressure-type wire connectors. |
|----------|---|

|                  |   |
|------------------|---|
| Special Features | Anti-oxidant and anti-seizing compound improves efficiency and service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service life of aluminum ele |
|------------------|---|

### Manufacturer Information

|       |       |
|-------|-------|
| Brand | Ideal |
|-------|-------|

|      |                |
|------|----------------|
| GTIN | 00783250300266 |
|------|----------------|

|     |              |
|-----|--------------|
| UPC | 783250300266 |
|-----|--------------|

### Taxonomies, Classifications, and Categories

|                      |                            |
|----------------------|----------------------------|
| Category Description | WIRE LUBE, MARKERS, & TIES |
|----------------------|----------------------------|

|      |                       |
|------|-----------------------|
| Type | Anti-Oxidant Compound |
|------|-----------------------|



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Package         | 10    |
| Weight Per each | 0.325 |

## Uses, Certifications, and Standards

|          |           |
|----------|-----------|
| standard | UL Listed |
|----------|-----------|