

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



30030 Noalox (8 Oz. Bottle)

Catalog Number	30030
Manufacturer	ldeal
Description	Anti-Oxidant Compound, 8 Oz Squeeze Bottle, Petroleum Base,
	1.04 Specific Gravity, 310 °F Flash Point, 0.6 LB
Weight per unit	0.6000 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Features

specific gravity 1.04

Dimensions and Weight

Size 8 OZ Squeeze Bottle

Descriptions

Description

Description	NONEON (O OZ. DOTTEL)
extra long description	IDEAL 30-030 NOALOX ANTI-OXIDANT 80
Features	IDEAL Noalox Anti-Oxidant compound improves efficiency and service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts. It is used with all types of pressure-type
	wire connectors.
	WII O COMMODICIO

NOALOX (8 OZ. BOTTLE)

Anti-oxidant and anti-seizing compound improves efficiency and service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service life of aluminum ele

Manufacturer Information

Special Features

Brand	Ideal
GTIN	00783250300303
UPC	783250300303

Taxonomies, Classifications, and Categories

Category Description	WIRE LUBE, MARKERS, & TIES	
Туре	Anti-Oxidant Compound	



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Package	10
Weight Per each	0.6
Uses, Certifications, and Standards	
standard	UL Listed