

## Elliott Electric Supply

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

We Deliver...Lower Cost, Quality Products, & Personal Service

33+SUPER34X76FT Super 33+ Vinyl Electrical Tape, 3/4" X 76', BK Minnesota Mining (3M)

Catalog Number	33+SUPER34X76FT
Manufacturer	Minnesota Mining (3M)
Description	"Scotch <sup>®</sup> Super 33+ Vinyl Electrical Tape, 3/4 In X 76 FT, 1 In
	Core, Black, 10 Rolls/Carton, 100 Rolls/Case"
Weight per unit	0.0027 (lbs/each)
Product Category	Tools & Testers
eatures	
Adhesive Type	Rubber
Dielectric Strength	1150
Elongation at Break	2.5
media	
Voltage Rating	600
laterial, Color, and Finish	
Backing Material	Polyvinyl Chloride
imensions and Weight	
Thickness	7
escriptions	
Description	SUPER 33+ VINYL ELECTRICAL TAPE, 3/4" X 76', BK
extra long description	3M 7100201470 Scotch <sup>®</sup> Super 33+™ Vi
Features	Scotch <sup>®</sup> Super 33+ <sup>™</sup> Vinyl Electrical Tape is a premium grade, 7 mil thick, all-weather vinyl-insulating tape. It is designed to
	perform continuously in ambient temperatures up to 105°C
	(220°F). The tape is conformable for cold weather application
	down to $-18^{\circ}$ C (0°F). It has excellent resistance to abrasion,
	moisture, alkalies, acids, corrosion and varying weather
	conditions (including ultraviolet exposure). The combination of
	elastic backing and aggressive adhesive provides moisture-tigh
	electrical and mec
Long Description	"Scotch® Super 33+ Vinyl Electrical Tape, 3/4 in x 76 ft, 1 in
- J F	Core,Black, 10 rolls/carton, 100 rolls/Case"
Product Type	Scotch <sup>®</sup> Super 33+ <sup>™</sup> Vinyl Electrical Tape
lanufacturer Information	
	Super 33+
Brand	Super 33+ 00638060290354
	Super 33+ 00638060290354 33+34X76FT1



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	ТАРЕ	
Packaging		
Carton	1	
Package	100	
Weight Per each	0.0027	
Uses, Certifications, and Standard		