

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



42201 Detect Ug"Caution Buried Electric Line" Red, 3" *Ideal*

| Catalog Number | 42201 |
|---------------------------------|---|
| Manufacturer | ldeal |
| Description | Detectable Underground Tape, 3 In Roll Width, 1000 FT Roll Length, Caution Buried Electric Line Below Legend, Solid Aluminum Foil Core, Red, Thickness: 5 Mil, Elongation: 80 PCT Astm D882-75B, Composition: Ideal Specs: Bottom Layer Pe, Top Layer Pet, Foil Industry Standard, Tensile Strength: 35 LB/In (15000 Psi) Astm D882, For Protection, Location and Identification Of Underground Utility Installations |
| Weight per unit | 6.2 (lbs/each) |
| Product Category | Markers & Marking Tapes |
| Features | |
| Legend | Caution Buried Electric Line Below |
| Material | Solid Aluminum Foil Core |
| Roll Length | 1000 |
| Material, Color, and Finish | |
| Color | Red |
| Dimensions and Weight Thickness | 5 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Descriptions | DETECT HOUSE HIT ON BURIER 5: 557515 1 11511 555 511 |
|---|---|
| Description | DETECT UG"CAUTION BURIED ELECTRIC LINE" RED, 3" |
| extra long description | IDEAL 42-201 Tape, Ideal, Detectable |
| Features | Our Detectable Underground Tapes are formulated to resist degradation from acid and alkali found in soils. Tape uses organic and lead-free ink pigments, and has a solid aluminum-foil core construction to protect, locate and identify underground utility installations. Tape meets or exceeds industry standards, includin the American Public Works Association (APWA) color code. |
| Long Description | Detectable Underground Tape, 3 IN Roll Width, 1000 FT Roll Length, Caution Buried Electric Line Below Legend, Solid Aluminum Foil Core, Red, Thickness: 5 MIL, Elongation: 80 PCT ASTM D882-75B, Composition: IDEAL Specs: Bottom Layer PE, Top Layer PET, Foil Industry Standard, Tensile Strength: 35 LB/IN (15000 PSI) ASTM D882, For Protection, Location And Identification Of Underground Utility Installations |
| Product Type | Tape, Ideal, Detectable Underground, LGND: Caution Buried Elec |
| Special Features | Solid aluminum foil core tapes for protection, location and identification of underground utility installations; Meets or exceeds industry standards including the American Public Works Association (APWA) color code; Formulated to resist degradation from acid and alkali found in soils; Lead-free pigments and organic lead-free ink |
| Manufacturer Information | |
| Brand | ldeal |
| GTIN | 00783250422012 |
| Manufacturers Part Number | 42-201 |
| UPC | 783250422012 |
| Taxonomies, Classifications, and Ca | itegories |
| Category Description | TAPE |
| Туре | Detectable Underground Tape |
| Packaging | |
| Carton | 1 |
| Weight Per each | 6.1666 |
| Uses, Certifications, and Standards Application | For Protection, Location And Identification Of Underground |

Utility Installations