

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per cap

## **46125 Quicksnap Nonmetallic Snap In Connector 1/2"125/JR** *Ideal*

| <b>電影館 大学</b>                      |   |
|------------------------------------|---|
| Catalog Number                     | 46125   |
| Manufacturer                       | Ideal   |
| Description                        | Ideal 46-125 Quicksnap Nonmetallic  |
| Weight per unit                    |   |
| Product Category                   | Wiring Devices  |
| Descriptions                       |   |
| Description                        | QUICKSNAP NONMETALLIC SNAP IN CONNECTOR 1/2"125/JR  |
| Features                           | The IDEAL Quick Snap connector provides exceptional performance and incredible value. Quick Snap can be installed quickly and easily, without the use of tools, securing cable in place and providing superior protection from damage that can be caused by rough knock-out edges. Simply push in - no tools required. Protects and secures cableSnap connector into 1/2" knockout Insert from the outsidePush non-metallic sheathed cable through connectorSecurely holds cable while protecting from rough edges of knockouts |
| Long Description                   | IDEAL 46-125 QuickSnap NonMetallic  |
| Product Type                       | Quicksnap Nonmetallic Snap In Connector 1/2 125 JR  |
| Manufacturer Information           |   |
| Brand                              | Ideal   |
| GTIN                               | 00783250677269  |
| Manufacturers Part Number          | 46-125  |
| UPC                                | 783250677269  |
| Taxonomies, Classifications, and ( | Categories  |
| Category Description               | Datacom Wiring Devices and Accessories  |
| Packaging                          |   |
| Carton                             | 1   |
| Package                            | 125   |
|                                    |   |

1.36