

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



standard

557 Scotchlok Electrical Idc 557-Pouch , RD *Minnesota Mining (3M)*

Soon	
Catalog Number	557
Manufacturer	Minnesota Mining (3M)
Description	3M™ Scotchlok™ Insulation Displacement Connector 557
	Provides A Dual Element Connection. The Connector Is
	Polypropylene Insulated and Used to Connect 2 Wires While
	Insulating The Connection. It Is Self Stripping and Flame
	Retardant.
Weight per unit	0.0030 (lbs/each)
Product Category	Small Terminals & Connectors
Descriptions	
Description	SCOTCHLOK ELECTRICAL IDC 557-POUCH ,RD
extra long description	3M 7100166937 3M™ Scotchlok™ IDC C
Features	3M™ Scotchlok™ Insulation Displacement Connector 557 is 600V
	rated for building wire and 1000V rated for signs, fixtures and
	luminaires. It withstands temperatures of 221 degrees F (105
	degrees C). UL Listed, CSA Certified and RoHS 2011/65/EU
	Compliant.
Long Description	3M [™] Scotchlok [™] Insulation Displacement Connector 557
	provides a dual element connection. The connector is
	polypropylene insulated and used to connect 2 wires while
D. J. J. T	insulating the connection. It is self stripping and flame retardant.
Product Type	3M™ Scotchlok™ Idc Connector 557
Special Features	Flame Retardant
Manufacturer Information	
Brand	Scotchlok
GTIN	00054007214946
Manufacturers Part Number	7100166937
UPC	054007214946
Taxonomies, Classifications, and Cate	egories
Category Description	WIRE NUTS
Туре	Insulation Displacement
Packaging	
Carton	100
Package	1000
Weight Per each	0.003
V	
Uses, Certifications, and Standards	

UL and CSA