

RECTORSEAL® LOW-VOC SOLVENT CEMENTS

Continued

Arctic™ 616L

○ Clear - medium body PVC solvent cement

| Code | Description | Qty. |
|-------|-------------|------|
| 55909 | ½ pt. | 24 |
| 55919 | 1 pt. | 12 |
| 55948 | 1 qt. | 12 |
| 55953 | 1 gal. | 4 |



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Formulated for use in cold weather
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

Application • Premium polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • Pipe up to 6" schedule 40; 1-¼" schedule 80 • Remains stable from 0°F to 120°F

Recommended for

- Potable water • Pressure pipe
- Gas • Conduit • Sewers
- DWV systems



Also available in gal. can

Pete™ 602L

○ Clear - medium body PVC solvent cement

| Code | Description | Qty. |
|-------|-------------|------|
| 55922 | ¼ pt. | 24 |
| 55924 | ½ pt. | 24 |
| 55926 | 1 pt. | 12 |
| 55928 | 1 qt. | 12 |
| 55916 | 1 gal. | 4 |



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Reduces product run-off
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For up to 6" for schedule 40; 1-¼" for schedule 80

Recommended for

- Potable water • Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



Gene™ 404L

○ Clear - regular body PVC solvent cement

| Code | Description | Qty. |
|-------|-------------|------|
| 55901 | ¼ pt. | 24 |
| 55902 | ½ pt. | 24 |
| 55904 | 1 pt. | 12 |
| 55906 | 1 qt. | 12 |
| 55908 | 1 gal. | 4 |



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Fast setting formula
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564
- Low-VOC

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • ABS to PVC non-pressured transition joints • Schedule 40 up to 2" pressure; up to 4" non-pressure pipe (DWV)

Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



RECTORSEAL® LOW-VOC SOLVENT CEMENTS

Continued

Arctic™ 616L

○ Clear - medium body PVC solvent cement

| Code | Description | Qty. |
|-------|-------------|------|
| 55909 | ½ pt. | 24 |
| 55919 | 1 pt. | 12 |
| 55948 | 1 qt. | 12 |
| 55953 | 1 gal. | 4 |



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Formulated for use in cold weather
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

Application • Premium polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • Pipe up to 6" schedule 40; 1-¼" schedule 80 • Remains stable from 0°F to 120°F

Recommended for

- Potable water • Pressure pipe
- Gas • Conduit • Sewers
- DWV systems



Also available in gal. can

Pete™ 602L

○ Clear - medium body PVC solvent cement

| Code | Description | Qty. |
|-------|-------------|------|
| 55922 | ¼ pt. | 24 |
| 55924 | ½ pt. | 24 |
| 55926 | 1 pt. | 12 |
| 55928 | 1 qt. | 12 |
| 55916 | 1 gal. | 4 |



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Reduces product run-off
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For up to 6" for schedule 40; 1-¼" for schedule 80

Recommended for

- Potable water • Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



Gene™ 404L

○ Clear - regular body PVC solvent cement

| Code | Description | Qty. |
|-------|-------------|------|
| 55901 | ¼ pt. | 24 |
| 55902 | ½ pt. | 24 |
| 55904 | 1 pt. | 12 |
| 55906 | 1 qt. | 12 |
| 55908 | 1 gal. | 4 |



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Fast setting formula
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564
- Low-VOC

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • ABS to PVC non-pressured transition joints • Schedule 40 up to 2" pressure; up to 4" non-pressure pipe (DWV)

Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems

