

# RECTORSEAL® LOW-VOC SOLVENT CEMENTS

Continued

## Arctic™ 616L

○ Clear - medium body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55909 | ½ pt.       | 24   |
| 55919 | 1 pt.       | 12   |
| 55948 | 1 qt.       | 12   |
| 55953 | 1 gal.      | 4    |



PW-G-DWV-SW



FILE NO. 1796

### FEATURES

- Formulated for use in cold weather
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Premium polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • Pipe up to 6" schedule 40; 1-¼" schedule 80 • Remains stable from 0°F to 120°F

### Recommended for

- Potable water • Pressure pipe
- Gas • Conduit • Sewers
- DWV systems



Also available in gal. can

## Pete™ 602L

○ Clear - medium body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55922 | ¼ pt.       | 24   |
| 55924 | ½ pt.       | 24   |
| 55926 | 1 pt.       | 12   |
| 55928 | 1 qt.       | 12   |
| 55916 | 1 gal.      | 4    |



PW-G-DWV-SW



FILE NO. 1796

### FEATURES

- Reduces product run-off
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For up to 6" for schedule 40; 1-¼" for schedule 80

### Recommended for

- Potable water • Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



## Gene™ 404L

○ Clear - regular body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55901 | ¼ pt.       | 24   |
| 55902 | ½ pt.       | 24   |
| 55904 | 1 pt.       | 12   |
| 55906 | 1 qt.       | 12   |
| 55908 | 1 gal.      | 4    |



PW-G-DWV-SW



FILE NO. 1796

### FEATURES

- Fast setting formula
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • ABS to PVC non-pressured transition joints • Schedule 40 up to 2" pressure; up to 4" non-pressure pipe (DWV)

### Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



# RECTORSEAL® LOW-VOC SOLVENT CEMENTS

Continued

## Arctic™ 616L

○ Clear - medium body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55909 | ½ pt.       | 24   |
| 55919 | 1 pt.       | 12   |
| 55948 | 1 qt.       | 12   |
| 55953 | 1 gal.      | 4    |



### FEATURES

- Formulated for use in cold weather
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Premium polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • Pipe up to 6" schedule 40; 1-¼" schedule 80 • Remains stable from 0°F to 120°F

### Recommended for

- Potable water • Pressure pipe
- Gas • Conduit • Sewers
- DWV systems



Also available in gal. can

## Pete™ 602L

○ Clear - medium body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55922 | ¼ pt.       | 24   |
| 55924 | ½ pt.       | 24   |
| 55926 | 1 pt.       | 12   |
| 55928 | 1 qt.       | 12   |
| 55916 | 1 gal.      | 4    |



### FEATURES

- Reduces product run-off
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For up to 6" for schedule 40; 1-¼" for schedule 80

### Recommended for

- Potable water • Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



## Gene™ 404L

○ Clear - regular body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55901 | ¼ pt.       | 24   |
| 55902 | ½ pt.       | 24   |
| 55904 | 1 pt.       | 12   |
| 55906 | 1 qt.       | 12   |
| 55908 | 1 gal.      | 4    |



### FEATURES

- Fast setting formula
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • ABS to PVC non-pressured transition joints • Schedule 40 up to 2" pressure; up to 4" non-pressure pipe (DWV)

### Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems

