

# RECTORSEAL® LOW-VOC SOLVENT CEMENTS

Continued

## Gold™ 844L

○ Clear - heavy body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55950 | ¼ pt.       | 24   |
| 55951 | ½ pt.       | 24   |
| 55952 | 1 pt.       | 12   |
| 55954 | 1 qt.       | 12   |
| 55955 | 1 gal.      | 4    |



PWG-DWV-SW



FILE NO. 1798

### FEATURES

- Excellent gap filling
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784

- For pipe up to 12" schedule 40 and schedule 80

### Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



## Hot™ 203L

● Blue - medium body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55988 | ¼ pt.       | 24   |
| 55989 | ½ pt.       | 24   |
| 55990 | 1 pt.       | 12   |
| 55993 | 1 qt.       | 12   |
| 55994 | 1 gal.      | 4    |



PWG-DWV-SW



FILE NO. 1798

### FEATURES

- Fast drying
- Excellent in cold weather
- LEED compliant
- 2 year shelf life
- Meets ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement joins both rigid and flexible PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specifications D1784 • For all rigid PVC classes up to 6" schedule 40 and 1-¼" schedule 80

### Recommended for

- Irrigation • Pools
- Spas • Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems • ENT
- Flexible PVC hose



See ordering chart for container sizes available.

## Homer™ 828L

○ Gray - heavy body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55960 | ½ pt.       | 24   |
| 55961 | 1 pt.       | 12   |
| 55963 | 1 qt.       | 12   |
| 55964 | 1 gal.      | 4    |



PWG-DWV-SW



FILE NO. 1798

### FEATURES

- Superior bonding strength
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For pipe up to 12" schedule 40 and schedule 80

• Remains stable from 40°F to 120°F

### Recommended for

- Potable water
- Pressure pipe
- Gas • Conduit
- Sewers
- DWV systems



Also available in gal. can

# RECTORSEAL® LOW-VOC SOLVENT CEMENTS

Continued

## Gold™ 844L

○ Clear - heavy body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55950 | ¼ pt.       | 24   |
| 55951 | ½ pt.       | 24   |
| 55952 | 1 pt.       | 12   |
| 55954 | 1 qt.       | 12   |
| 55955 | 1 gal.      | 4    |



PWG-DWV-SW



FILE NO. 1798

### FEATURES

- Excellent gap filling
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784

- For pipe up to 12" schedule 40 and schedule 80

### Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



## Hot™ 203L

● Blue - medium body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55988 | ¼ pt.       | 24   |
| 55989 | ½ pt.       | 24   |
| 55990 | 1 pt.       | 12   |
| 55993 | 1 qt.       | 12   |
| 55994 | 1 gal.      | 4    |



PWG-DWV-SW



FILE NO. 1798

### FEATURES

- Fast drying
- Excellent in cold weather
- LEED compliant
- 2 year shelf life
- Meets ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement joins both rigid and flexible PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specifications D1784 • For all rigid PVC classes up to 6" schedule 40 and 1-¼" schedule 80

### Recommended for

- Irrigation • Pools
- Spas • Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems • ENT
- Flexible PVC hose



See ordering chart for container sizes available.

## Homer™ 828L

○ Gray - heavy body PVC solvent cement

| Code  | Description | Qty. |
|-------|-------------|------|
| 55960 | ½ pt.       | 24   |
| 55961 | 1 pt.       | 12   |
| 55963 | 1 qt.       | 12   |
| 55964 | 1 gal.      | 4    |



PWG-DWV-SW



FILE NO. 1798

### FEATURES

- Superior bonding strength
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

**Application** • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For pipe up to 12" schedule 40 and schedule 80

- Remains stable from 40°F to 120°F

### Recommended for

- Potable water
- Pressure pipe
- Gas • Conduit
- Sewers
- DWV systems



Also available in gal. can