ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

55985 QT MED PVC CONDIT 633L LOW VOC

RECTORSEAL

Catalog Number	55985
Manufacturer	RECTORSEAL
Description	Solvent Cement, 1 QT, Dauber Top Bottle, Clear, Pungent Odor, 0.91 Specific Gravity, -17 °C;+4.1 °F Flash Point, 27 lb
Weight per unit	N/A
Product Category	Paint, Chemicals, Etc.

Descriptions

Description	QT MED PVC CONDIT 633L LOW VOC
Long Description	QT MED PVC CONDIT 633L LOW VOC
Product Type	Electrical Conduit Cement
Extra Long Description	LOW-VOC, MEDIUM TYPE; CLEAR COLOR; ASTM D2564, NSF, UPC APPLICABLE STANDARD; PVC ELECTRICAL CONDUIT APPLICATION; DAUBER TOP CAN CONTAINER TYPE; 6 INCH DIAMETER (SCHEDULE 40/80) PIPE SIZE; 1 PINT CONTAINER SIZE; LEED COMPLIANT; ODOR PUNGENT; SPECIFIC GRAVITY 0.91; BOILING POINT 151 DEG F; FLASH POINT 4.1 DEG F; VAPOR DENSITY 2.5; VAPOR PRESSURE 129 MM HG AT 68 DEG F; EVAPORATION RATE 8 TO 14.5; SHELF LIFE 2 YEAR

Manufacturer Information

Brand	
GTIN	00021449559850
UPC	889966

Taxonomies, Classifications, and Categories

Category Description	ADHESIVES

Packaging

Carton	1
Package	12
Weight Per Each	N/A

PVC ELECTRICAL CONDUIT CEMENT 633L

Low VOC PVC Solvent Cement

Description | Characteristics | Applications | Packaging | Instructions | Precautions | Specifications | Limited Warranty

DESCRIPTION:

PVC Electrical Conduit Cement 633L is specially formulated for use on polyvinyl chloride (PVC) conduit Types I and II. It is a medium body cement in clear or gray to match conduit color.
Max VOC per SCAQMD 1168/316A or BAAQMD Method 40: 510 g/l.
Top of Page

CHARACTERISTICS:

- Medium body - thick formula to reduce product run off
- Excellent gap filling characteristics
- Exceeds ASTM D 2564 specifications
- Medium fast setting allows corrections before setting up
- LEED Compliant
- NSF approved formula (clear only)

Top of Page

APPLICATIONS:

PVC Electrical Conduit Cement 633L is designed for use on PVC conduit Types I and II up to and including 6" for Schedule 40 and Schedule 80.
Top of Page

PACKAGING:

Clear Code	Gray Code	Size	Qty. Per Case	Lbs. per Case	Cu. Ft Per Case
55980	---------	1/2 pint dauber top (237 ml)	24 cans	16	.45
55983	55995	Pint dauber top (473 ml)	12 cans	15	.43
55985	55996	Quart dauber top (946 ml)	12 cans	27	.78
55986	55997	Gallon can (3.8 L)	4 cans	35	.80

Top of Page

INSTRUCTIONS:

1. Store and apply between 40 degree F and 120 degree F. Protect from freezing. Use Arctic™ for applications below 40 degree F. Do not use if cement has become curdled, lumpy, thickened or is beyond two years from date stamped on container. Do not thin.
2. **Wear non-permeable gloves during application to avoid skin contact.**
3. Clean fitting socket and conduit and check for proper fit. Apply PRIMER to all PVC surfaces. Primer not required on non-metallic electrical conduit. While still wet, quickly begin solvent cement application.
4. Shake well before using and stir frequently while using. Apply with supplied dauber applicator. For conduit greater than 2" diameter, use natural bristle brush sized to 1/2 of the conduit diameter.
5. Apply thin coat evenly to socket. Avoid Puddling. Quickly apply heavy coat to conduit end. While wet, quickly insert pipe into fitting with slight twisting movement until it bottoms out.
6. Hold conduit into fitting for at least 30 seconds to prevent pipe from backing out.
7. Wipe excess cement from joint with rag. Allow 15 minutes before handling. Avoid full-line pressure for 24 hours. Cure time varies with size, fit, temperature and humidity.

For additional technical information, call Toll Free 1-800-231-3345.

Top of Page

PRECAUTIONS:

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,

CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

D A N G E R!

EXTREMELY FLAMMABLE • HARMFUL OR FATAL IF SWALLOWED
VAPOR HARMFUL • EYE AND SKIN IRRITANT • MAY BE ABSORBED THROUGH SKIN
VAPORS MAY CAUSE FLASH FIRES

CONTAINS: Tetrahydrofuran, Methyl Ethyl Ketone, Cyclohexanone and Acetone.
PRECAUTIONS: Vapors are heavier than air and can collect in low areas.Keep away from heat, sparks, and flames until vapors are gone. Use only with good cross-ventilation. Wear adequate protective gear and clothing. Avoid breathing vapors and contact with skin, eyes and clothing. Long term repeated overexposure to solvents may cause damage to the brain, nervous system, reproductive system, respiratory system, mucous membranes, liver, and kidneys. Wash after handling. **FIRST AID**: For any overexposure, get immediate medical attention after first aid is given. **Eyes** - Flush 15 minutes with clean water. **Skin** - Wash with soap and water. **Inhalation** - Remove to fresh air. **Ingestion** - DO NOT INDUCE VOMITING. Only if conscious, give large amounts of water. Do not reuse empty container. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Material Safety Data Sheet.

Top of Page

SPECIFICATIONS:

Wt/Gal @ 77 degree F	7.6+- .2 lbs/gal.
Flash Point SETA CC	4.1 degree F
Color	Clear or Gray
Shelf Life	2 years. Subject to inspection

NSF. UPC ® (Clear only)

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Top of Page

LIMITED WARRANTY:

RectorSeal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.

Top of Page

RectorSeal®
2601 Spenwick Drive • Houston, TX 77055 USA
713-263-8001 • Fax 713-263-7577
Toll-free 800-231-3345 • Fax 800-441-0051

Back to Solvent Cements