

# METACAULK® FIRESTOP DEVICES

Continued

## Cover Guard™

Fire-rated gasket for electrical boxes

Code	Description	Qty.
66270	Double receptacle	50
66272	Single receptacle	50
66274	Double switch	50
66276	Single switch	50
66265	Single decor	50
66266	Double decor	50



### FEATURES

- Reduces sound transmission
- Easy to install
- Highly intumescent
- STC rating 54

**Application** • A single component fire-rated gasket for use with electrical boxes to comply with the "24 inch rule" • Fits under the cover plate and does not take up volume



US Patent No. 6,207,085; 6,252,167 & 7,348,484

## Box Guard™

Fire-rated pad for electrical boxes

Code	Description	Qty.
66366	Single box	50
66367	Double box	50
66369	4-11/16" x 4-11/16"	50



### FEATURES

- Adheres to back of electrical box
- Non-conductive
- Highly intumescent
- STC rating 53

**Application** • One component fire-rated for use in electrical boxes • It is inserted on the inside back wall of an electrical box prior to wiring



US Patent No. 6,207,085 & 6,252,167

## Putty Sticks & Pads

Fire-rated putty

Code	Description	Qty.
66345	18 cu./in. - stick	12
66340	6" x 7" x 1/8" thick	20
66335	7" x 7" x 1/8" thick	20



### FEATURES

- Applied by hand
- No asbestos fillers
- Pads - STC rating 60
- For interior use
- Adheres to all common building surfaces

**Application** • Putty sticks are used to seal around penetrating items through fire-rated walls, floors and within blank openings

• Putty pads are used to maintain the hourly rating of fire-rated walls containing electrical outlet boxes and to reduce sound transmission • Hand moldable with no curing time



Sound Transmission Class (STC) rating - Tested in a UL 411 wall assembly/section to ASTM E90

# METACAULK® FIRESTOP DEVICES

Continued

## Cover Guard™

Fire-rated gasket for electrical boxes

Code	Description	Qty.
66270	Double receptacle	50
66272	Single receptacle	50
66274	Double switch	50
66276	Single switch	50
66265	Single decor	50
66266	Double decor	50

**Application** • A single component fire-rated gasket for use with electrical boxes to comply with the "24 inch rule" • Fits under the cover plate and does not take up volume



US Patent No. 6,207,085; 6,252,167 & 7,348,484



### FEATURES

- Reduces sound transmission
- Easy to install
- Highly intumescent
- STC rating 54

## Box Guard™

Fire-rated pad for electrical boxes

Code	Description	Qty.
66366	Single box	50
66367	Double box	50
66369	4-11/16" x 4-11/16"	50

**Application** • One component fire-rated for use in electrical boxes • It is inserted on the inside back wall of an electrical box prior to wiring



US Patent No. 6,207,085 & 6,252,167



### FEATURES

- Adheres to back of electrical box
- Non-conductive
- Highly intumescent
- STC rating 53

## Putty Sticks & Pads

Fire-rated putty

Code	Description	Qty.
66345	18 cu./in. - stick	12
66340	6" x 7" x 1/8" thick	20
66335	7" x 7" x 1/8" thick	20

**Application** • Putty sticks are used to seal around penetrating items through fire-rated walls, floors and within blank openings

• Putty pads are used to maintain the hourly rating of fire-rated walls containing electrical outlet boxes and to reduce sound transmission • Hand moldable with no curing time



### FEATURES

- Applied by hand
- No asbestos fillers
- Pads - STC rating 60
- For interior use
- Adheres to all common building surfaces

Sound Transmission Class (STC) rating - Tested in a UL 411 wall assembly/section to ASTM E90

Contact: RectorSeal®

713-263-8001 | 800-231-3345

713-263-7577 | 800-441-0051

www.rectorseal.com