

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



690G Combo 2SW 1P 15A 120/277V W/GRD BN

Pass & Seymour/Legrand

Catalog Number	690G	
Manufacturer	Pass & Seymour/Legrand	
Description	Combination Switch, 1 Pole, 15 A, 120/277 V Ac, Brown, 1.32 (L)	
	X 0.94 (W) X 3.28 (H) In, Toggle Actuator, Wall Mount, 0.22 LB	
Weight per unit	0.2162 (lbs/each)	
Product Category	Combination Devices	

Features

action	(2) SP
actuator	Toggle
amperage rating	15
connection	Side wire
Contact Rating	15amp, 120/277vac
operating cycles	30000 30000
Poles	Single Pole
Voltage Wattage	Electrical power is expressed in Amps and Volts.

Dimensions and Weight

	•		
Size		1.32 L x 0.94 W x 4.06 H	

Descriptions

Description	COMBO 25W 1P 15A 120/277V W/GRD BN
extra long description	P&S 690G COMBO 2SW 1P 15A 120/277V
Special Features	Easily accessible break-off for separate or common feed. Side
·	wire #12 and #14 AWG. Two devices fit into the space of one.
	Grounding combination devices meet NEC Requirements.

Manufacturer Information

Brand	Pass and Seymour
GTIN	00785007690026
Manufacturers Part Number	690G
UPC	785007690026

Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Туре	COMBINATION

Trade Size

Amnorago	1	5	:	1	^
Amperage	ı	·	J.	٠,	u

Packaging

Carton	10	
Package	50	
Weight Per each	0.2162	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

environmental conditions	Flammability: UL94 V2
Mounting	WALL
Operating Temperature	Maximum continuous +60°C, minimum -30°C
standard	CULUS, UL20