


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## **7030BSL 120V Ac Smoke & Carbon Monoxide Alarm With Led STR** *BRK Brands/Ademco/First Alert*

Catalog Number	7030BSL
Manufacturer	BRK Brands/Ademco/First Alert
Description	Hardwired Combo Smoke & CO Alarm With 10-Year Sealed Lithium Battery Backup. Includes 177 Candela Led Strobe Light. Ac 120V Interconnectable With Silence and Latching Features. Includes Photoelectric Smoke Sensing Technology and Electrochemical Carbon Monoxide Sensor.
Weight per unit	
Product Category	•
Features	
alarm type	Audio
dimensions	5.6" diameter x 2.0" height
Operating Voltage	•
Output Current	, i
Sensor Type	Dhata / Flastrashamiasl
Temperature Range	40 Degree F (4 Degree C) to 100 Degree F (38 Degree C)
Material, Color, and Finish	
Color	White
Enclosure Material	Plastic
Descriptions	
Description	120V AC SMOKE & CARBON MONOXIDE ALARM WITH LED STR
extra long description	BRK 1038870 ALRM 3IN1 7030BSL SMK-C
Features	Hardwired Combo smoke & CO alarm with 10-Year sealed lithium battery backup. Includes 177 candela LED Strobe light.
Long Description	Hardwired Combo smoke & CO alarm with 10-Year sealed lithium battery backup. Includes 177 candela LED Strobe light. AC 120V Interconnectable with Silence and Latching features. Includes Photoelectric smoke sensing technology and electrochemical carbon monoxide sensor.
Product Type	Alrm 3IN1 7030BSL SMK-CO-Strbe Ac/DC 10y
Manufacturer Information	
Brand	BRK
GTIN	00029054018137
Manufacturers Part Number	1038870
UPC	029054018137



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and	
Category Description	SMOKE DETECTORS
Туре	Combination Strobe, Smoke & Carbon Monoxide Alarm
Packaging	
Carton	1
Package	6
Weight Per each	0.872
Uses, Certifications, and Standard	ds
Application	Single and or multiple station strobe alarm specifically designed to detect smoke and carbon monoxide in residential and institutional applications including sleeping rooms of hospitals, hotels, motels, dormitories and other multi-family dwellings.
environmental conditions	10 percent to 90 percent relative humidity (RH)
Mounting	mounts to wall or ceiling
standard	UL217, UL2034