





GE  
Lighting

**41865 - 7613**

GE PAR36 - Emergency Building Light; Emergency Building



**GENERAL CHARACTERISTICS**

Lamp Type	Sealed Beam - PAR
Bulb	PAR36
Base	Screw Terminals
Filament	C-6
Rated Life	50.0 hrs
Primary Application	Emergency Building Light; Emergency Building

**PHOTOMETRIC CHARACTERISTICS**

Beam Spread - Horizontal	30.0 - 10.0 °
Beam Spread - Vertical	20.0 - 10.0 °
Max. Beam Candlepower (MBCP) (MAX)	400.0

**ELECTRICAL CHARACTERISTICS**

Wattage	8.0
Voltage	6.0

**DIMENSIONS**

Maximum Overall Length (MOL)	2.7500 in(69.8 mm)
Bulb Diameter (DIA)	4.500 in(114.3 mm)

**PRODUCT INFORMATION**



Product Code	41865
Description	7613
ANSI Code	7613
Standard Package	Case
Standard Package GTIN	00043168418652
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168962278



GE  
Lighting

**41865 - 7613**

GE PAR36 - Emergency Building Light; Emergency Building



**GENERAL CHARACTERISTICS**

Lamp Type	Sealed Beam - PAR
Bulb	PAR36
Base	Screw Terminals
Filament	C-6
Rated Life	50.0 hrs
Primary Application	Emergency Building Light; Emergency Building

**PHOTOMETRIC CHARACTERISTICS**

Beam Spread - Horizontal	30.0 - 10.0 °
Beam Spread - Vertical	20.0 - 10.0 °
Max. Beam Candlepower (MBCP) (MAX)	400.0

**ELECTRICAL CHARACTERISTICS**

Wattage	8.0
Voltage	6.0

**DIMENSIONS**

Maximum Overall Length (MOL)	2.7500 in(69.8 mm)
Bulb Diameter (DIA)	4.500 in(114.3 mm)

**PRODUCT INFORMATION**

Product Code	41865
Description	7613
ANSI Code	7613
Standard Package	Case
Standard Package GTIN	00043168418652
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168962278