

## Fluorescent Lampholders Shallow Base



### T8 & T12 Slimline Single Pin Fluorescent Sockets



**80-1496 Plunger**  
1 3/4" H x 1 1/4" W x 1 1/4" Dia.



**80-1497 Fixed**  
1 3/4" H x 1 1/4" W x 1 1/4" Dia.

Shallow Base  
Slide-On Quickwire for  
Wet and Damp Locations  
Rapid Start for 20 Gauge Panels  
Strip 3/8" - 1/2"  
660W-1000V

### High Output 800 MA -1500 MA — Recessed Double Contact



**80-2129 Plunger**  
2 1/4" H x 1 1/4" W x 1 1/2" Dia.



**80-2130 Fixed**  
2 1/4" H x 1 1/4" W x 1 1/2" Dia.

Shallow Base  
for Slide On Quickwire  
Power Groove and  
Jacketed Lamps  
20 Gauge Panels  
Strip 3/8" - 1/2"  
660W-600V

### T8 & T12 (HO) High Output Fluorescent Sockets - Recessed Double Contact



**80-1498 Plunger**  
1 7/8" H x 1 3/8" W x 1 1/4" Dia.



**80-1499 Fixed**  
1 7/8" H x 1 3/8" W x 1 1/4" Dia.

Quickwire Terminals  
Accept Up To 18 Gauge  
Solid or Tinned Leads  
Slide-On Shallow Base  
Rapid Start  
Strip 3/8" - 1/2"  
660W-1000V

## Fluorescent Lampholders Shallow Base



### T8 & T12 Slimline Single Pin Fluorescent Sockets



**80-1496 Plunger**  
1 3/4" H x 1 1/4" W x 1 1/4" Dia.



**80-1497 Fixed**  
1 3/4" H x 1 1/4" W x 1 1/4" Dia.

Shallow Base  
Slide-On Quickwire for  
Wet and Damp Locations  
Rapid Start for 20 Gauge Panels  
Strip 3/8" - 1/2"  
660W-1000V

### High Output 800 MA -1500 MA — Recessed Double Contact



**80-2129 Plunger**  
2 1/4" H x 1 1/4" W x 1 1/2" Dia.



**80-2130 Fixed**  
2 1/4" H x 1 1/4" W x 1 1/2" Dia.

Shallow Base  
for Slide On Quickwire  
Power Groove and  
Jacketed Lamps  
20 Gauge Panels  
Strip 3/8" - 1/2"  
660W-600V

### T8 & T12 (HO) High Output Fluorescent Sockets - Recessed Double Contact



**80-1498 Plunger**  
1 7/8" H x 1 3/8" W x 1 1/4" Dia.



**80-1499 Fixed**  
1 7/8" H x 1 3/8" W x 1 1/4" Dia.

Quickwire Terminals  
Accept Up To 18 Gauge  
Solid or Tinned Leads  
Slide-On Shallow Base  
Rapid Start  
Strip 3/8" - 1/2"  
660W-1000V