

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# 8300WMRI Hosp GRD Dup Recp 20A 125V Mri W

Pass & Seymour/	Legrand
-----------------	---------

Catalog Number	8300WMRI
Manufacturer	Pass & Seymour/Legrand
Description	Extra Heavy-Duty Hospital Grade Mri Duplex Receptacle Back and Side-Wire 20A 125V
Weight per unit	0.1667 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro

#### **Features**

20
Back and side wire
Withstands 2000V minimum
Nylon
3
Double Pole
125.0 V
125
Electrical power is expressed in Amps and Volts.
14 - 10

# Material, Color, and Finish

Color	White
-------	-------

### **Dimensions and Weight**

Height	3.281
Width	.900

### **Descriptions**

boulptions	
Description	HOSP GRD DUP RECP 20A 125V MRI W
extra long description	P&S 8300WMRI HOSP GRD DUP RECP 20A
Long Description	Extra Heavy-Duty Hospital Grade MRI Duplex Receptacle Back and Side-Wire 20A 125V
Product Type	Hosp GRD Dup Recp 20A 125V Mri W
Special Features	Designed expressly for MRI applications. Exclusive patented feature, circuit label on face allows permanent circuit identification. Extra heavy-duty one-piece nickel-plated brass mounting strap with integral ground for superior structural integrity and long-term performance036 inch thick, brass, triple-wipe power contacts for lasting retention. Strap tabs wrap around and lock down on face to prevent strap from separating from face and back body. Easily accessed break-off, line-contact connecting tab for



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

1 /1 /	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	・ヘヘキロ	IPAPI	ntari	nation

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007269178
Manufacturers Part Number	8300WMRI
UPC	785007269178

# **Taxonomies, Classifications, and Categories**

Category Description	Residential Switches
Type	Hospital Grade MRI Receptacle, Extra Heavy-Duty

### **Trade Size**

Amperage 20.0

### **Packaging**

onagg		
Carton	1	
Package	100	
Weight Per each	0.1667	

### Uses, Certifications, and Standards

Application	Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
nema rating	5-20R
standard	CULUS, FEDSPEC, UL498, CSA C22.2 No. 42
Temperature Rating	-40° - 60° C