

Category Cables



96963

Siamese (Dual) Cat 5e Cables

Part Number	Description	UL Type	Weight (Nom.)	Outside Dia. (Nom.)	Packaging	Jacket Color
96963	(2) Cat 5e 24/4pr BC Tested to 350 MHz	CM	51 lbs	0.185" x 0.370"	1,000' Reel (06)	Blue (06)



96203

Category 3 Cables

Part Number	Description	Pairs	UL Type	Weight (Nom.)	Outside Dia. (Nom.)	Packaging	Jacket Color
96202	Cat 3 24/2pr solid BC ETL Verified	2	CMR	10 lbs	0.140"	1,000' Box (46)	Gray (09) Beige (33)
96203	Cat 3 24/3pr solid BC ETL Verified	3	CMR	14 lbs	0.150"	1,000' Box (46)	Gray (09) Beige (33)
96204	Cat 3 24/4pr solid BC ETL Verified	4	CMR	17 lbs	0.180"	1,000' Box (46)	Gray (09) Beige (33)
96206	Cat 3 24/6pr solid BC	6	CMR	25 lbs	0.200"	1,000' Box (46)	Gray (09)
996212	Cat 3 24/12pr solid BC	12	CMR	53 lbs	0.320"	1,000' Reel (06)	Gray (09)
96210	Cat 3 24/25pr solid BC	25	CMR	108 lbs	0.410"	1,000' Reel (06)	Gray (09)
76214	Cat 3 24/4pr solid BC ETL Verified, Plenum Rated	4	CMP	19 lbs	0.160"	1,000' Box (46)	Gray (09) Natural (23)

96204

96206

Freq. (MHz)	Attn. (dB/100m) Max	NEXT loss (dB) Min	Ret. Loss (dB) Max
1	2.6	41	12
4	2.6	32	12
8	2.6	27	12
10	2.6	26	12
16	2.6	23	10

Category Cables



96963

Siamese (Dual) Cat 5e Cables

Part Number	Description	UL Type	Weight (Nom.)	Outside Dia. (Nom.)	Packaging	Jacket Color
96963	(2) Cat 5e 24/4pr BC Tested to 350 MHz	CM	51 lbs	0.185" x 0.370"	1,000' Reel (06)	Blue (06)



96203

Category 3 Cables

Part Number	Description	Pairs	UL Type	Weight (Nom.)	Outside Dia. (Nom.)	Packaging	Jacket Color
96202	Cat 3 24/2pr solid BC ETL Verified	2	CMR	10 lbs	0.140"	1,000' Box (46)	Gray (09) Beige (33)
96203	Cat 3 24/3pr solid BC ETL Verified	3	CMR	14 lbs	0.150"	1,000' Box (46)	Gray (09) Beige (33)
96204	Cat 3 24/4pr solid BC ETL Verified	4	CMR	17 lbs	0.180"	1,000' Box (46)	Gray (09) Beige (33)
96206	Cat 3 24/6pr solid BC	6	CMR	25 lbs	0.200"	1,000' Box (46)	Gray (09)
996212	Cat 3 24/12pr solid BC	12	CMR	53 lbs	0.320"	1,000' Reel (06)	Gray (09)
96210	Cat 3 24/25pr solid BC	25	CMR	108 lbs	0.410"	1,000' Reel (06)	Gray (09)
76214	Cat 3 24/4pr solid BC ETL Verified, Plenum Rated	4	CMP	19 lbs	0.160"	1,000' Box (46)	Gray (09) Natural (23)



96204



96206

Freq. (MHz)	Attn. (dB/100m) Max	NEXT loss (dB) Min	Ret. Loss (dB) Max
1	2.6	41	12
4	2.6	32	12
8	2.6	27	12
10	2.6	26	12
16	2.6	23	10