



9716SW8808

## INDOOR REPLACEMENT ROUND POWER SUPPLY CORDS

- Temperature Rating of -40°F to 140°F (-40°C to 60°C)
- 125 Voltage Rating
- Common Applications: Vacuum, Electric Drill, Work Light

| Stock #    | Gauge/Conductors | Wire Type | Length (ft) | Length (m) | Cord Color | Amps | Case Pack Quantity |
|------------|------------------|-----------|-------------|------------|------------|------|--------------------|
| 9702SW8808 | 16/2             | SJTW      | 6'          | 1.8 m      | Black      | 13   | 25                 |
| 9703SW8808 | 16/3             | SJTW      | 3'          | 0.9 m      | Black      | 13   | 25                 |
| 9706SW8808 | 16/3             | SJTW      | 6'          | 1.8 m      | Black      | 13   | 25                 |
| 9709SW8808 | 16/3             | SJTW      | 9'          | 2.7 m      | Black      | 13   | 25                 |
| 9716SW8808 | 14/3             | SJTW      | 6'          | 1.8 m      | Black      | 15   | 25                 |
| 9719SW8808 | 14/3             | SJTW      | 9'          | 2.7 m      | Black      | 15   | 25                 |



9734SW8809

## INDOOR REPLACEMENT FLAT POWER SUPPLY CORDS

- Temperature Rating of -40°F to 140°F (-40°C to 60°C)
- 125 Voltage Rating
- Common Applications: Microwave, Refrigerator, Dehumidifier

| Stock #    | Gauge/Conductors | Wire Type      | Length (ft) | Length (m) | Cord Color | Amps | Case Pack Quantity |
|------------|------------------|----------------|-------------|------------|------------|------|--------------------|
| 9723SW8809 | 16/3             | SPT-3          | 3'          | 0.9 m      | Gray       | 13   | 25                 |
| 9733SW8809 | 16/3             | SPT-3 Straight | 3'          | 0.9 m      | Gray       | 13   | 25                 |
| 9724SW8809 | 16/3             | SPT-3 R/Angle  | 4'          | 1.2 m      | Gray       | 13   | 25                 |
| 9734SW8809 | 16/3             | SPT-3 Straight | 4'          | 1.2 m      | Gray       | 13   | 25                 |
| 9726SW8809 | 16/3             | SPT-3 R/Angle  | 6'          | 1.8 m      | Gray       | 13   | 25                 |
| 9736SW8809 | 16/3             | SPT-3 Straight | 6'          | 1.8 m      | Gray       | 13   | 25                 |
| 9743SW8823 | 14/3             | SPT-3 Straight | 3'          | 0.9 m      | Beige      | 15   | 25                 |
| 9743SW09   | 14/3             | SPT-3 Straight | 3'          | 0.9 m      | Gray       | 15   | 25                 |
| 9746SW8823 | 14/3             | SPT-3 Straight | 6'          | 1.8 m      | Beige      | 15   | 25                 |
| 98700009   | 12/3             | SPT-3          | 6'          | 1.8 m      | Beige      | 15   | 25                 |



3533SW3323

## INDOOR MAJOR APPLIANCE REPLACEMENT CORDS

- Temperature Rating of -4°F to 140°F (-20°C to 60°C)
- 125 Voltage Rating (250 Voltage Rating for 3537SW8809)
- Common Applications: Air Conditioner, Space Heater, Refrigerator

| Stock #     | Gauge/Conductors | Wire Type | Length (ft) | Length (m) | Cord Color | Amps | Case Pack Quantity |
|-------------|------------------|-----------|-------------|------------|------------|------|--------------------|
| 3531SW3323  | 14/3             | SPT-3     | 3'          | 0.9 m      | Beige      | 15   | 36                 |
| 3531SW09    | 14/3             | SPT-3     | 3'          | 0.9 m      | Gray       | 15   | 24                 |
| 3532SW3323  | 14/3             | SPT-3     | 6'          | 1.8 m      | Beige      | 15   | 24                 |
| 3532SW09    | 14/3             | SPT-3     | 6'          | 1.8 m      | Gray       | 15   | 24                 |
| 3533SW3323  | 14/3             | SPT-3     | 9'          | 2.7 m      | Beige      | 15   | 18                 |
| 3535SW3323  | 14/3             | SPT-3     | 12'         | 3.7 m      | Beige      | 15   | 12                 |
| 3536SW3323  | 14/3             | SPT-3     | 15'         | 4.6 m      | Beige      | 15   | 12                 |
| 3537SW8809* | 12/3             | SPT-3     | 9'          | 2.7 m      | Gray       | 20   | 18                 |

\*6-20 P/R



9716SW8808

## INDOOR REPLACEMENT ROUND POWER SUPPLY CORDS

- Temperature Rating of -40°F to 140°F (-40°C to 60°C)
- 125 Voltage Rating
- Common Applications: Vacuum, Electric Drill, Work Light

| Stock #    | Gauge/Conductors | Wire Type | Length (ft) | Length (m) | Cord Color | Amps | Case Pack Quantity |
|------------|------------------|-----------|-------------|------------|------------|------|--------------------|
| 9702SW8808 | 16/2             | SJTW      | 6'          | 1.8 m      | Black      | 13   | 25                 |
| 9703SW8808 | 16/3             | SJTW      | 3'          | 0.9 m      | Black      | 13   | 25                 |
| 9706SW8808 | 16/3             | SJTW      | 6'          | 1.8 m      | Black      | 13   | 25                 |
| 9709SW8808 | 16/3             | SJTW      | 9'          | 2.7 m      | Black      | 13   | 25                 |
| 9716SW8808 | 14/3             | SJTW      | 6'          | 1.8 m      | Black      | 15   | 25                 |
| 9719SW8808 | 14/3             | SJTW      | 9'          | 2.7 m      | Black      | 15   | 25                 |



9734SW8809

## INDOOR REPLACEMENT FLAT POWER SUPPLY CORDS

- Temperature Rating of -40°F to 140°F (-40°C to 60°C)
- 125 Voltage Rating
- Common Applications: Microwave, Refrigerator, Dehumidifier

| Stock #    | Gauge/Conductors | Wire Type      | Length (ft) | Length (m) | Cord Color | Amps | Case Pack Quantity |
|------------|------------------|----------------|-------------|------------|------------|------|--------------------|
| 9723SW8809 | 16/3             | SPT-3          | 3'          | 0.9 m      | Gray       | 13   | 25                 |
| 9733SW8809 | 16/3             | SPT-3 Straight | 3'          | 0.9 m      | Gray       | 13   | 25                 |
| 9724SW8809 | 16/3             | SPT-3 R/Angle  | 4'          | 1.2 m      | Gray       | 13   | 25                 |
| 9734SW8809 | 16/3             | SPT-3 Straight | 4'          | 1.2 m      | Gray       | 13   | 25                 |
| 9726SW8809 | 16/3             | SPT-3 R/Angle  | 6'          | 1.8 m      | Gray       | 13   | 25                 |
| 9736SW8809 | 16/3             | SPT-3 Straight | 6'          | 1.8 m      | Gray       | 13   | 25                 |
| 9743SW8823 | 14/3             | SPT-3 Straight | 3'          | 0.9 m      | Beige      | 15   | 25                 |
| 9743SW09   | 14/3             | SPT-3 Straight | 3'          | 0.9 m      | Gray       | 15   | 25                 |
| 9746SW8823 | 14/3             | SPT-3 Straight | 6'          | 1.8 m      | Beige      | 15   | 25                 |
| 98700009   | 12/3             | SPT-3          | 6'          | 1.8 m      | Beige      | 15   | 25                 |



3533SW3323

## INDOOR MAJOR APPLIANCE REPLACEMENT CORDS

- Temperature Rating of -4°F to 140°F (-20°C to 60°C)
- 125 Voltage Rating (250 Voltage Rating for 3537SW8809)
- Common Applications: Air Conditioner, Space Heater, Refrigerator

| Stock #     | Gauge/Conductors | Wire Type | Length (ft) | Length (m) | Cord Color | Amps | Case Pack Quantity |
|-------------|------------------|-----------|-------------|------------|------------|------|--------------------|
| 3531SW3323  | 14/3             | SPT-3     | 3'          | 0.9 m      | Beige      | 15   | 36                 |
| 3531SW09    | 14/3             | SPT-3     | 3'          | 0.9 m      | Gray       | 15   | 24                 |
| 3532SW3323  | 14/3             | SPT-3     | 6'          | 1.8 m      | Beige      | 15   | 24                 |
| 3532SW09    | 14/3             | SPT-3     | 6'          | 1.8 m      | Gray       | 15   | 24                 |
| 3533SW3323  | 14/3             | SPT-3     | 9'          | 2.7 m      | Beige      | 15   | 18                 |
| 3535SW3323  | 14/3             | SPT-3     | 12'         | 3.7 m      | Beige      | 15   | 12                 |
| 3536SW3323  | 14/3             | SPT-3     | 15'         | 4.6 m      | Beige      | 15   | 12                 |
| 3537SW8809* | 12/3             | SPT-3     | 9'          | 2.7 m      | Gray       | 20   | 18                 |

\*6-20 P/R