



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



A10060217 BLK FM PRTTV Cap *Crouse-Hinds*

| | |
|------------------|---|
| Catalog Number | A10060217 |
| Manufacturer | Crouse-Hinds |
| Description | Eaton Crouse-Hinds Series Cam-Lok J Series E1016 Protective Cap, Up to 400A Continuous, Black, Female, Thermoplastic Elastomer (Tpe), Lanyard, 600 Vac/DC |
| Weight per unit | 1.0 (lbs/each) |
| Product Category | Misc Wiring Devices |

Features

| | |
|------------|-----------------------------------|
| dimensions | 1.5000 IN X 1.5000 IN X 2.4600 IN |
|------------|-----------------------------------|

Descriptions

| | |
|------------------------|---|
| Description | BLK FM PRTTV CAP |
| extra long description | CRS-H A100602-17 E1016 F PROT CAP W |
| Features | The Cam-Lok J series from Eaton's Crouse-Hinds Division provides the means to quickly connect and disconnect power systems safely. Cam-Lok is the industry standard for motors, generators, indoor and outdoor lighting distribution panels, and numerous other power applications. |
| Long Description | Eaton Crouse-Hinds series Cam-Lok J Series E1016 protective cap, Up to 400A continuous, Black, Female, Thermoplastic elastomer (TPE), Lanyard, 600 Vac/dc |
| Product Type | E1016 F Prot Cap W/Cord BK |
| Special Features | NEMA 3R Enclosure |

Manufacturer Information

| | |
|---------------------------|---------------------------|
| Brand | EATON CROUSE-HINDS SERIES |
| GTIN | 00662275101242 |
| Manufacturers Part Number | A100602-17 |
| UPC | 662275101242 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|----------------------|
| Category Description | Pin & Sleeve Devices |
| Type | Protective Cap |

Packaging

| | |
|-----------------|---|
| Carton | 1 |
| Weight Per each | 1 |

Uses, Certifications, and Standards

| | |
|--------------------------|---|
| Application | Ind Facilities & Factories - Facility: Power Distribution and Control |
| environmental conditions | -40 To 105 Deg C |
| standard | CSA |