

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Size

A6D10R 600V 10A RK1 TD Fuse

Mersen Fuses

Catalog Number	A6D10R
Manufacturer	Mersen Fuses
Description	Fuse A6D-R - Class RK1 - Time-Delay 600VAC 600VDC 10A Ferrule Smartspot® Amp-Trap 2000®
Weight per unit	0.1400 (lbs/each)
Product Category	Current Limiting
Features	
AC Voltage Rating	600
amperage rating	10
class	Class RK1
connection	Ferrule
interrupt rating	200
type of indicators	SmartSpot®
Voltage Rating	600
Material, Color, and Finish	
Body Material	PolyTube
Dimensions and Weight	

5 x 0.81



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_	•		
11000	rin	TIA	nc
Desc			
-			

Description	600V 10A RK1 TD FUSE
extra long description	Mersen A6D10R Fuse A6D-R - Class RK
Features	Amp-Trap 2000® time-delay A6D-R fuses provide IEC Type 2 "no damage" protection to existing mains, feeders, and branch circuits serving motor and non-motor loads. A6D-R fuses will open fast enough under extreme fault conditions for maximum short circuit protection to prevent damage to motor starters, switches, and other circuit components, yet also provide the time-delay needed for motor in-rush currents. A6D-R fuses can be used to replace older 600V Class H, K or RK5 fuses already installed in the field.
Long Description	Fuse A6D-R - Class RK1 - Time-Delay 600VAC 600VDC 10A Ferrule SmartSpot® Amp-Trap 2000®
Product Type	Fuse A6D-R - Class RK1 - Time-Delay 600VAC 600VDC 10A Ferrul
Short Description	600V 10A RK1 TD FUSE
Special Features	Non-indicating or Solid state SmartSpot visual blown fuse indicator Time-delay for motor starting and transformer inrush currents without nuisance opening 600VAC & 600VDC dual rated 300kA interrupting rating - self-certified, UL witnessed tests Extremely current-limiting for low peak let-thru current Recommended for Arc Flash energy reduction Easy 2-to-1 selectivity for prevention of nuisance shut downs and "black outs" Rejection-style design prevents replacement errors (when used with recommended fuse blo
nufacturer Information	Mersen

Mar

Brand	Mersen	
GTIN	00782001991807	
Manufacturers Part Number	A6D10R	
UPC	782001991807	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	CLASS RK1

Packaging

Carton	1
Package	10
Weight Per each	0.14



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Motors Safety switches Transformers Branch circuit protection
	Disconnects Control panels All general-purpose circuits
Mounting	Clip
standard	UL listed to standard 248-12 File E2137 DC listed to UL standard
	248 CSA certified to standard C22.2 No. 248.12