

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## AF52301114 54A, 250-500V, 3P Contactor Industrial Connections &

Industrial Connections	&
Catalog Number	AF52301114
Manufacturer	Industrial Connections &
Description	AF52 Contactors Are Used For Controlling Power Circuits Up to 690 V Ac and 220 V DC. They Are Mainly Used For Controlling 3-Phase Motors, Non-Inductive or Slightly Inductive Loads. Af Contactors Include An Electronic Coil Interface Accepting A Wide Control Voltage Uc Min Uc Max. Only Four Coils Cover Control Voltages Between 24500 V 50/60 HZ or 20500 V DC. Af Contactors Can Manage Large Control Voltage Variations. One Coil Can Be Used For Different Control Voltages Used Worldwide Without Any
Weight per unit	2.4 (lbs/each)
Product Category	IEC Contactors
Descriptions	
Description	54A, 250-500V, 3P CONTACTOR
extra long description	ABB AF52-30-11-14 CTR,3P,54A,250-50
Long Description	AF52 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF contactors include an electronic coil interface accepting a wide control voltage Uc min Uc max. Only four coils cover control voltages between 24500 V 50/60 Hz or 20500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any
Product Type	CTR, 3P, 54A, 250-500VAC/DC, 2/2
Manufacturer Information	
Brand	ABB
GTIN	00888614119871
Manufacturers Part Number	AF52-30-11-14
UPC	888614119871
Taxonomies, Classifications, and Category Description	Categories IEC/FREEDOM CONTACTOR
Packaging	
Carton	1
Weight Per each	2.3899
•	