

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AL250N 250 AI/Cu 2 Hole Compression Lug *Nsi Industries*

Catalog Number	AL250N
Manufacturer	Nsi Industries
Description	2HOLESTANDARD Barrelaluminum Compression Lug 250 MCM -1/2 Bolt Standard Barrelaluminum Compression Lugs Is A Type Ofaluminum Compression Connector That Is Produced From High Conductivityaluminum Tubing.Center Stop Assures Proper Cable Installation.They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference. Listed For 35KV Maximum When Properly Installed.
Weight per unit	0.2200 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Cable Size	250 MCM (STR)
Material	Aluminum
Number of Holes	2
Stud Size	1/2
Voltage Rating	600 V
Warranty	
Material, Color, and Finish	
Color	Red
Finish	Tin Plated Bronze
Dimensions and Weight Size	L=5.30 - W=1.25 - OD=.920 - ID=.590



Mounting standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

250 AL/CU 2 HOLE COMPRESSION LUG
NSI AL250N AL/CU CMP Lug 4/0 AWG Ne
2HoleStandard BarrelAluminum Compression Lug 250 MCM -1/2 Bolt Standard BarrelAluminum Compression Lugs is a type ofaluminum compression connector that is produced from high conductivityaluminum tubing. Center stop assures proper cable installation. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
2HoleStandard BarrelAluminum Compression Lug 250 MCM -1/2 Bolt Standard BarrelAluminum Compression Lugs is a type ofaluminum compression connector that is produced from high conductivityaluminum tubing. Center stop assures proper cable installation. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
AI/Cu CMP Lug 4/0 Awg Nema MTG Spacing
250 MCM (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing
NSi
00662381031044
AL250N
662381031044
egories
Comp & Mech Lugs and Butt Splices
Standard Barrel - Two Hole
1
12
0.22
Terminate, Splice, Tap Power Connectors
90 C

UL486A/B

1/2 Mounting Holes