

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **APPT50A 1/2IN Cond Body** *Appleton/Oz Gedney*

| APPT50A   |
|---|
| Appleton/Oz Gedney  |
| Form 85 Unilets Type T Conduit Outlet Body, Hub Size: 1/2 In,   |
| Form: 85, Length: 4-3/4 In, Height: 1.38 In, Material: Pressure   |
| Cast Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered   |
| Female Threaded, Standard: UI 514A, UI 514B, UI File  |
| 0.2750 (lbs/each)   |
| Alum  |
|   |
| Tapered Female Threaded   |
| 85  |
| Pressure Cast Aluminum  |
|   |
| Epoxy Powder Coat   |
|   |
| 1.38  |
| 1/2   |
| 4-3/4   |
|   |
| 1/2IN COND BODY   |
| APP T50A 1/2 FORM 85 UNILET   |
| Form 85 UNILETS Type T Conduit Outlet Body, Hub Size: 1/2 IN, Form: 85, Length: 4-3/4 IN, Height: 1.38 IN, Material: Pressure   |
| Cast Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered Female Threaded, Standard: UL 514A, UL 514B, UL File  |
| 1/2 Form 85 Unilet (A)  |
| Accurately tapped, tapered threads for tight, rigid joints and excellent ground continuity; Allow connections for branch runs; Connect and change direction of conduit runs; Form 85 copperfree aluminum Unilets are lightweight, self oxidizing, self-renewing and offer a high corrosion resistance; Internal volume and maximum wire capacity clearly marked on castings; Lightweight aluminum facilitates shipping, handling and installing; Make bends in conduit system; Permit access to conductors for maintenance; Provide ope |
|   |



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| и |            | _ |   | 1 |   | _ 1 |    |           |     | <b>.</b> |      |    |    |   | _        |
|---|------------|---|---|---|---|-----|----|-----------|-----|----------|------|----|----|---|----------|
| ľ | ۱ <i>۱</i> | - | n |   | - | СТ  |    | ·Δr       | ın  | TO       | ۱rr  | ทว | TI | n | <b>7</b> |
|   | v          |   |   | u | а | L.I | uı | <b>CI</b> | 'In | H.V.     | ,, , | па |    | u |          |
|   |            |   |   |   |   |     |    |           |     |          |      |    |    |   |          |

| Brand                     | Appleton       |
|---------------------------|----------------|
| GTIN                      | 00781381686808 |
| Manufacturers Part Number | T50A           |
| UPC                       | 781381686808   |

#### **Taxonomies, Classifications, and Categories**

| Category Description | Fuses & Fuse Accessories   |
|----------------------|----------------------------|
| Туре                 | Type T Conduit Outlet Body |

#### **Packaging**

| ,,,ag.,,g       |       |  |
|-----------------|-------|--|
| Carton          | 10    |  |
| Package         | 50    |  |
| Weight Per each | 0.275 |  |

#### Uses, Certifications, and Standards

| Application | For Use With Rigid Steel, Rigid Aluminum Conduit, IMC And EMT |
|-------------|---|
| standard    | UL 514A, UL 514B, UL File Number E2527, CSA C22.2 No. 18.3,   |
|             | CSA 065183, NEMA FB-1   |