



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



ATQ1410 500V 1-4/10A TD Midget Fuse

Mersen Fuses

Catalog Number	ATQ1410
Manufacturer	Mersen Fuses
Description	Fuse Atq - Midget - Time-Delay 500VAC 1.4A Ferrule Amp-Trap®
Weight per unit	0.0120 (lbs/each)
Product Category	Small Dimension Fuses

Features

AC Voltage Rating	500
amperage rating	1.4
class	Midget
connection	Ferrule
interrupt rating	10
Voltage Rating	500

Material, Color, and Finish

Body Material	GMG
---------------	-----

Dimensions and Weight

Size	1.5 x 0.41
------	------------

Descriptions

Description	500V 1-4/10A TD MIDGET FUSE
extra long description	Mersen ATQ1-4/10 Fuse ATQ - Midget
Features	Amp-Trap ATQ midget time-delay fuses are rated 500VAC with 42 ampere ratings from 1/10 to 30A. They are an excellent choice for supplemental protection of circuits where the available short circuit current does not exceed 10,000A. (Not for Branch Circuit Protection)
Long Description	Fuse ATQ - Midget - Time-Delay 500VAC 1.4A Ferrule Amp-Trap®
Product Type	Fuse Atq - Midget - Time-Delay 500VAC 1.4A Ferrule
Short Description	500V 1-4/10A TD MIDGET FUSE
Special Features	Numerous ratings for a wide variety of applications up to 500VAC Time-delay (12 seconds at 200 percent rating) for circuits with high inrush current Can be used with UltraSafe™ Fuse holders 1 1/2" x 13/32" (10 mm x 38 mm) dimensions

Manufacturer Information

Brand	Mersen
GTIN	00782001903510
Manufacturers Part Number	ATQ1-4/10
UPC	782001903510



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description.....MIDGET FUSES

Type.....Midget Fuses

Packaging

Carton.....1

Package.....10

Weight Per each.....0.012

Uses, Certifications, and Standards

Application.....Supplemental protection of lighting, solenoid, motor and
transformer circuits

Mounting.....Clip

standard.....UL listed to standard 248-14 File E33925 CSA Certified to
Standard C22.2 No. 248.14