ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



# B11 B-Cap Wire Connector, B1 Yellow, 100/Box

*Ideal*

| | |
|---|---|
| Catalog Number | B11 |
| Manufacturer | Ideal |
| Description | Wire Connector, (2) #20 Awg Conductor Size, (3) #12 Awg Conductor Size, Yellow Insulation Color, +221 °F Operating Temperature, 2 to 6 Conductors, 600 V Ac, 0.01 LB |
| Weight per unit | 0.7000 (lbs/each) |
| Product Category | Electrical Fixture Conn ( Nuts |

## Features

| | |
|---|---|
| Material | Flame-retardant Polypropelene |
| Voltage Rating | 600 |

## Material, Color, and Finish

| | |
|---|---|
| Color | Yellow |

## Descriptions

| | |
|---|---|
| Description | B-CAP WIRE CONNECTOR, B1 YELLOW, 100/BOX |
| Features | The B-CAP Wire Connector gets you in those hard-to reach spots comfortably, especially when you’re retrofitting or updating. Slim, classic fins and an expanding interior spring give the B-CAP a secure grip with extra leverage, making it the most compact connector on the market for up to 5 #12 (Red Model B2).The unique, space-saving profile of the B-CAP makes it perfect for retrofit work and shallow boxes.The B-CAP also features a tough, flame-retardant shell that withstands environmental extremes with a de |

## Manufacturer Information

| | |
|---|---|
| Brand | Buchanan |
| GTIN | 00781789451886 |
| UPC | 781789451886 |

## Taxonomies, Classifications, and Categories

| | |
|---|---|
| Category Description | Datacom Wiring Devices and Accessories |

## Availability

| | |
|---|---|
| Manufacturer Status | Inactive |
| minimum qty | 100 |
| Status | Inactive |

## Packaging

| | |
|---|---|
| Carton | 100 |
| Package | 1000 |
| Weight Per cap | 0.7 |

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

## Uses, Certifications, and Standards

| | |
|---|---|
| Application | Insulating or Joining 1 or more conductors |
| environmental conditions | Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F) |
| standard | CSA C22.2 #188, UL 486C Listed, RoHS |