

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



B22SHAGALV20 BLTD 1-5/8X3-1/4X240 12GA GLV BK2BK SLTD, 2" CNTR Cooper B-Line/Cable Tray

| Catalog Number | B22SHAGALV20 |
|-----------------------------|--|
| Manufacturer | Cooper B-Line/Cable Tray |
| Description | Eaton B-Line Series Strut Back-to-Back Welded Channel, 1.62" H 2 240" L X 1.62" W, Steel, Pre-Galvanized, Sha, 12 Gauge |
| Weight per unit | 1.9 (lbs/each) |
| Product Category | Channel & Strut |
| eatures | |
| dimensions | 240.0000 IN X 1.6200 IN X 1.6200 IN |
| gauge | 12 |
| Grade | 33 |
| slot size | 1-1/8 In Length X 9/16 In Width |
| Material, Color, and Finish | |
| Finish | Pre-Galvanized |
| material composition | Cold Formed Low Carbon Steel |
| material standard | ASTM A653 SS |
| Dimensions and Weight | |
| Depth | 3-1/4 ln |
| Length | 20 ft |
| Width | 1-5/8 in |
| Descriptions | |
| Also Known As | Strut |
| | Strut channel |
| Description | BLTD 1-5/8X3-1/4X240 12GA GLV BK2BK SLTD, 2" CNTR |
| extra long description | B-LINE B22SHA-240GLV CHNL, 1 5/8" X |
| Features | Eaton offers a wide range of back to back and welded configured strut combinations for a variety of support applications. |
| Long Description | Eaton B-Line series strut back-to-back welded channel, 1.62" H x |
| Long Bosonphon | 240" L x 1.62" W, Steel, Pre-galvanized, SHA, 12 Gauge |
| Product Type | CHNL, 1 5/8" X 1 5/8", B to B, 9/16" X 7/8" Slots, 12 Ga |
| similar brands | Unistrut |
| Special Features | 2 In Center Spacing |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00781011034467 |
| Manufacturers Part Number | B22SHA-240GLV |
| UPC | 781011034467 |



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Taxonomies, Classifications, and Cate | egories |
|---------------------------------------|--|
| Category Description | STRUT CHANNEL |
| Туре | Strut back-to-back welded channel |
| Availability | |
| Status | Inactive |
| Packaging | |
| Carton | 1 |
| Weight | 3.64 Lb/Ft |
| Weight Per each | 1.85 |
| Uses, Certifications, and Standards | |
| Application | Generation - Renewable Energy - Alternative EnergyUtilityOther IT and Datacom - Other InfrastructuresGeneration - Conventional Energy - Conventional EnergyDatacenters - Datacenters - OtherCommercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - OtherInd Facilities & Factories - Facility - OtherCommercial / Institutional Buildings / Structures - Commercial/Inst Bldg Strctures - AftermarketResidential Bldgs & Facilities - Residential Bldgs & |

Facilities - OtherWa

Not Applicable