

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## BJ3200 Type BJ BRKR 200A/3 Pole 240V 10K Req 6 Spaces Eaton Corp

Catalog Number	BJ3200
Manufacturer	Eaton Corp
Description	Eaton Type BJ 1-Inch Plug-On Main Breakers, Type BJ 1-Inch Plug-On Main Breakers, 200 A, 10 Kaic, Three-Pole, 240V, BJ, Common Breaker Trip, #2 Awg-300 Kcmil Cu/Al, BJ
Weight per unit	3.2 (lbs/each)
Product Category	3 Pole Standard Trip Plug-In
Features	
dimensions	8.0000 IN X 3.5000 IN X 3.5000 IN
interrupt rating	10
Poles	3
Voltage Rating	240 V - 240 V
Descriptions	
Description	Type bj Brkr 200A/3 Pole 240V 10K REQ 6 Spaces
extra long description	ETN BJ3200 BJ 200A/3 Pole 240V 10K
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton Type BJ 1-Inch Plug-on Main Breakers, Type BJ 1-Inch plug-on main breakers, 200 A, 10 kAIC, Three-pole, 240V, BJ, Common breaker trip, #2 AWG-300 kcmil Cu/AI, BJ
Product Type	BJ 200A/3 Pole 240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00786676368452
Manufacturers Part Number	BJ3200
UPC	786676368452
Taxonomies, Classifications, and	
Category Description	MAIN BREAKERS
Туре	Thermal magnetic circuit breakers
Packaging Carton	1

3.2



2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

oo, commoditions, and chandand	
Application	OtherGeneration - Conventional Energy - Conventional
	EnergyDatacenters - IT Space: CI and Hyper ConvergedMarine
	Vessels and Equipment - Marine Vessels and Equipment -
	OtherGeneration - Renewable Energy - Alternative Energy
standard	UL 489, Federal Specifications Classification W-C375