



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



BR115AF BR Fireguard AfcI 1 Pole 15 Amp *Eaton Corp*

| | |
|------------------|-------------------------------------|
| Catalog Number | BR115AF |
| Manufacturer | Eaton Corp |
| Description | Etn BR115AF BR115AF66C1111G01BR Fir |
| Weight per unit | 0.7800 (lbs/each) |
| Product Category | 1P Special Application Plug-In |

Features

| | |
|------------------|-------------|
| amps | 15 |
| interrupt rating | 10 kAIC |
| Poles | Single-pole |
| Voltage Rating | 120/240 V |

Dimensions and Weight

| | |
|--------|------|
| Height | 1.25 |
| Length | 3 |
| Width | 4.75 |

Descriptions

| | |
|------------------|---|
| Description | BR FIREGUARD AFCI 1 POLE 15 AMP |
| Features | Eaton's residential BR Circuit Breakers are used in load centers, panelboards, or similar devices. They are made for a wide range of applications and include: BR 1" circuit breakers and accessories for BR-style load centers; arc fault circuit interrupters (AFCI); and ground fault circuit interrupters (GFCI). |
| Long Description | ETN BR115AF BR115AF66C1111G01BR FIR |
| Product Type | BR115AF66C1111G01BR Fireguard AfcI 1 Pole 15 Amp |
| Special Features | Arc fault |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Eaton |
| GTIN | 00782114231494 |
| Manufacturers Part Number | BR115AF |
| UPC | 782114231494 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|------------------------------------|
| Category Description | Fault Sensing Breakers (AFCI/GFCI) |
| Type | AFCI circuit breakers |

Availability

| | |
|---------------------|----------|
| Manufacturer Status | Inactive |
| Status | Inactive |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton 1

Weight Per each 0.78

Uses, Certifications, and Standards

standard UL 1699