

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

BRH120 Type BR BRKR 20A/1 Pole 120/240V 22K Eaton Corp

Catalog Number	BRH120
Manufacturer	Eaton Corp
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BR Style 1-Inch Plug-On Circuit Breaker, 20 A, 22 Kaic, Single-Pole, 120/240V, BRH, #14-4 Awg Cu/Al, BRH, Type BR Loadcenters
Weight per unit	0.3000 (lbs/each)
Product Category	1 Pole Standard Trip Plug-In
Features	
dimensions	1.0000 IN X 2.8000 IN X 2.5000 IN
interrupt rating	22 kAIC
Poles	1
Voltage Rating	120/240 V
Descriptions	
Description	TYPE BR BRKR 20A/1 POLE 120/240V 22K
extra long description	ETN BRH120 Type BR Breaker 20A/1 Po
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR thermal magnetic circuit breaker, Type BR style 1-Inch plug-on circuit breaker, 20 A, 22 kAIC, Single-pole, 120/240V, BRH, #14-4 AWG Cu/AI, BRH, Type BR Loadcenters
Product Type	Type BR Breaker 20A/1 Pole 120/240V 22K
Special Features	Used with Type BR Loadcenters
Manufacturer Information	
Brand	Eaton
GTIN	00786676373104
Manufacturers Part Number	BRH120
UPC	786676373104
Taxonomies, Classifications, and (Categories
Category Description	
Туре	_
Packaging	
33	

1

0.3

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

es, cei illications, and st	andarus
Application	OtherGeneration - Conventional Energy - Conventional
	EnergyDatacenters - IT Space: CI and Hyper ConvergedMarine
	Vessels and Equipment - Marine Vessels and Equipment -
	OtherGeneration - Renewable Energy - Alternative Energy
standard	UL 490, Federal Specifications Classification W-C376