ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



BT4SC0 15.1" Nyln CBL Tie SS Barb STD Cross Sec BLCK

Panduit Corporation

Catalog Number	BT4SC0
Manufacturer	Panduit Corporation
Description	The Dome-Top® BT4S-C0 Cable Tie Provides Dependable Bundling For Indoor/Outdoor Routing and Organization Requiring Uv and Weather Resistance. Standard Cross Section, 15.1 In (384MM) Long With 50 LB (222 N) Minimum Loop Tensile Strength and A 0.06–4 In (1.5–101.6MM) Bundle Diameter Range. It Is Black Nylon 6.6 (Uv-Resistant, Weather-Resistant). Operating Range -76 to 185°F (-60 to 85°C). Use With GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, and STH2 Tools.
Weight per unit	0.0070 (lbs/each)
Product Category	Cable Ties & Wraps

Features

media	Yes
Tensile Strength	50

Dimensions and Weight

Length	15.1
Thickness	0.05

Descriptions

Description	15.1" NYLN CBL TIE SS BARB STD CROSS SEC BLCK
extra long description	PAN BT4S-C0 Cable Tie, Black UV PA6
Long Description	The Dome-Top® BT4S-C0 cable tie provides dependable bundling for indoor/outdoor routing and organization requiring UV and weather resistance. Standard cross section, 15.1 in (384mm) long with 50 lb (222 N) minimum loop tensile strength and a 0.06–4 in (1.5–101.6mm) bundle diameter range. It is black Nylon 6.6 (UV-Resistant, Weather-Resistant). Operating range -76 to 185°F (-60 to 85°C). Use with GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, and STH2 tools.
Product Type	Cable Tie, Black Uv PA6.6, 15.1"L (384MM), 50LB, PK100
Special Features	Indoor/Outdoor

Manufacturer Information

Brand	PANDUIT
GTIN	00074983412280
Manufacturers Part Number	BT4S-C0
UPC	074983412280

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type	Cable Tie

Availability

minimum qty	100

Packaging

Carton	100
Package	1000
Weight Per each	0.007

Uses, Certifications, and Standards

standard	UL 62275 (File E56854), CSA-C22.2 No. 62275 (File 31212), Cert 05968/C0, BV File ACE 14/601/01 Product Code: 2535H, 89/60111 (E3), 11130200, QPL-AS23190, RoHS Compliant