

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## C6 #6 Cu Long Barrel Compression Butt Splice

	Nsi Industries	arrei Compression Butt Spiice
Catalog Number		C6
Manufacturer		Nsi Industries
Description		Compression Splice Connector, #8 Awg Conductor Size, #6 Awg Conductor Size, Non-Insulated, Copper Conductor Material, Blue Insulation Color, 2 Conductors, +90 °C Operating Temperature, 1.752 In Overall Length, Compression Terminal, 600 V, 0.04 LB/Ea
Weight per unit		0.0400 (lbs/cosb)
Product Category		Large Terminals & Connectors
Features		
Material		Copper
Number of Conductors		2
Poles		1
Voltage Rating		600 V
Warranty		1 VEAD
Material, Col	or, and Finish	
Color		Blue
Finish		Tin Plated
Dimensions a	and Weight	
Size		L=1.75 - OD=.300 - ID=.200
Descriptions		
Description Description		#6 CU LONG BARREL COMPRESSION BUTT SPLICE
•		NSLC 6 Facy Twict Closed End Conn
extra long description Features		Long Barrel TinnedCopperSplice6 AWG Long Barrel Tinned
routuros		CopperSplices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Manufacture	r Information	1
GTIN		00662381037503
UPC		662381037503
	Classifications and	
Taxonomies, Classifications, and C Category Description		Ones of Market and ID H Calling
Туре		· · · · · · · · · · · · · · · · · · ·
Packaging		
Carton		1
Package		100
		0.04

0.04

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A/B, UL467 (8 AWG -3/0 AWG)
Temperature Rating	90 C