


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





sub brand

**UPC** 

## **CHF220SW 2P 20A 240V TF Switching Neutral Breaker** *Eaton Corp*

	0.15000011
Catalog Number	CHF220SW
Manufacturer	Eaton Corp
Description	Switching Neutral Breaker, 20 A, Common Tripping Mechanism, Line and Load Lug Terminal, Plug-In, 120/240 V Ac, 0.42 In Overall Height, 1.5 In Overall Length, 5 In Overall Width
Weight per unit	1.0 (lbs/each)
Product Category	2P Special Application Plug-In
eatures	
amperage rating	20
class	1.0000 IN X 1.0000 IN X 2.2300 IN
Contact Configuration	Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other
Cord Type	Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other
element	Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other
Poles	2
Тгір Туре	Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other
used with	Type CH Loadcenters
Wire Size	#14-8 AWG Cu/Al
laterial, Color, and Finish	
Style	Open Office, Retail
imensions and Weight	
Height	3.5
Length	1.5
Width	5
escriptions	
Description	2P 20A 240V TF SWITCHING NEUTRAL BREAKER
extra long description	ETN CH220SW
Manufacturer Information	
GTIN	00782113101781
series	Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other

782113101781

Open Office, Retail



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	Specialty Breakers (Quad, Dupl, Shunt Trip)
Availability	
Manufacturer Status	Inactive
Packaging Carton	1
Weight Per each	1
Uses, Certifications, and Standards standard	UL 489